

PRIMARY CORNER DESCRIPTION Sec. Cor for 6, 7; 1 & 12 of T29-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6453)

Set a post, cor. of secs. 1, 6, 7, 12, from which

- A Red fir, 16" diam., bears N.45°W., 29 lks.
- A Red fir, 18" diam., bears N.65°E., 70 lks.
- A Laurel, 8" diam., bears S.50°E., 20 lks.
- A Laurel, 7" diam., bears S.35°W., 75 lks.

G.G. Stewart, Surveyor - Wit: G. Keller; C. Voytilla - Approx. 1921 - C.S. 47/165; C.S. 47/155; C.S. 6/18; Vol. 3 Pg.96

Find one BT and stump of other.

Set corner from the two BT's. Iron pipe from which:

- A 12" Fir bears N.15°W., 13.0 ft.
- A 14" Fir bears S.14½°W., 41.2 ft.
- A 14" Fir bears S.48°E., 28.0 ft.
- A 36" Fir bears N.65°E., 45.0 ft.

BLM Resurvey by Hans W. Thielsen - under group # 346 - surveyed Apr/May 1957 (DCSO records Vol.28 Page 12146)

Found corner as perpetuated by the County Surveyor in 1921 with an iron pipe 3/4" diam., 4" above ground, firmly set, from which an original bearing tree:

- A sawed fir stump, 36" diam., bears N.65°E., 68 lks., plainly blazed and healed. (Rec. dist., 70 lks.)

and trees marked by County Surveyor:

- A sawed fir stump, 18" diam., bears S.48°E., 43 lks., marked with healed blaze.
- A sawed fir stump, 16" diam., bears S.14½°W., 62 lks., with faint scribe marks visible on opened blaze.
- A sawed fir stump, 15" diam., bears N.15°W., 19 lks., plainly blazed and healed.

At the corner point

Set an iron post, 3 ft. long, 2" diam., 28" in the ground with brass cap marked:

T29S
R7W R6W
S 1 S 6
S12 S 7
1957

from which new bearing trees,

- A fir, 15" diam., bears N.10½°E., 55 lks., marked T29S R6W S6 BT.
- A fir, 12" diam., S.59°E., 77 lks., mkd T29S R6W S7 BT.
- A fir 10" diam., bears S.75°W., 144 lks., mkd T29S R7W S12 BT.

(Cont. Next Page)

