

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION Tsp. Cor. (NW Cor. Sec. 6)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5697)

Set post cor. to Tps. 28 and 29, between Rs. 6 and 7 West, from which

- A Laurel 6" dia., bears S.30°W., 27 lks.
- A Y.Oak 15" dia., bears S.22°E., 83 lks.
- A Y.Oak 14" dia., bears N.22°E., 48 lks.
- A Laurel 10" dia., bears N.71¼°W., 60 lks.

H.L. Eppstein, Co. Surveyor - Wit: Harry McCabe; Nichols; Smith - Jan. 25, 1928 - C.S. File 7/45

Set corner from old BT which were all in place, but trees in SE and NW quadrant reversed, bearing & distance alright. Marked following trees:

- Oak N.71°15'W., 56.1 ft. Old tree.
- Fir 14" dia., bears N.22°E., 39 ft.
- Fir 12" dia., bears S.71°30'E., 10 ft.
- Fir 15" dia., bears S.63°30'W., 33 ft.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; S.A. Bilow - Nov. 17, 1958 - C.S. File 49/50-11

Found - Orig. NW BT, I find 24" Oak snag, I open & find good scribing, "S36 BT".

I do not find other orig. BTs. I do find partly rotted Laurel stump that was opened years ago, no scribing found today, rec. S.22°E., 54.2 ft., I find to be S.26°E., 51.0 ft. I believe these are the BTs found by Eppstein, 1928. All of Eppstein's BTs have been cut & no scribing can be found on any stump, except I do find good scribing on SW BT which is in slide area and far out of position. I find 18" cut Fir in slide area scribed for SE BT. The evidence I find of Eppstein's BTs do not agree with original nor do they come to a common corner. Therefore, I use the original record bearing and distance from NW BT to set corner, N.71¼°W., 39.6 ft.

Set Brass cap at cor. mkd: County Surveyor's Office, 1958

S36|S31 T28S
S 1|S 6 T29S
R7W R6W

New BTs -15" R.Fir bears N.27°E., 55.6 ft. scribed T28S R6W
S31 CS BT.

15" R.Fir bears N.28°W., 47.9 ft. scribed T28S R7W
S36 CS BT.

13" R.Fir bears S.54°W., 124.6 ft. scribed T29S R7W S1
CS BT (cont. next page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION Tsp. Cor. (NW Cor. Sec. 6)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

No trees near to SE.
Cor. bears N.50°W., 11.0 ft. from intersection of N. running fence from E & W. fence.

Doug. County Surveyors Office - Randall Smith; Stephen Flause
Feb. 6, 1990 - C.S. File 64/5-11

Found - 1958 DCSO 2½" dia. brass cap on a 1¼" O.D. I.P. which protrudes 16" above ground.

Orig. 10" Laurel now 24" dia. at base 3 ft. high rotted Oak stump with axe mark (mix-up in orig. record, bears N.71¼°W., 39.6 ft. (agrees with orig. and 1958 possible problem with dist. in Eppstein's cor.

15" now 20" dia., D.Fir with a fully healed double blaze, bears N.27°E., 55.6 ft.

15" now 23" dia. D.Fir with a fully healed double blaze bears N.28°W., 47.9 ft.

13" now 18" dia. D.Fir with a fully healed double blaze, bears N.28°W., 124.6 ft.

18" dia. 4 ft. high rotted D.Fir stump, previously opened with illegible scribing visible, blaze faces west, stump is in a slide area, bears S.60°W., 54.7 ft. (One of Eppstein's BTs.)

SE BT of Eppstein looked for, not found. Other BTs by Eppstein not looked for.

New BT - 12" Madrone bark scribed "T29S R6W S6 CS BT" bears S.43°E., 39.0 ft.

Corner lies on a westerly slope.

DCSO-GIS Corner visitation - 4/14/2004 - Typed: 1/31/2011 -
C.S. File 67/33-1

Monument - BC/IP - 1.25"
Comment - ok

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-23 A-C

FOUND - 2½" brass cap stamped COUNTY SURVEYORS OFFICE 1958
26" Fir with healed face and tag dated 5/61;
N.27°E., 55.6'
16" Madrone with healed face and tag dated 2/5/90;
S.43°E., 39.0'
30" Fir with healed face and tag dated 5/61;
N.28°W., 47.9'