

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 129100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 6 only T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6460-61)

Set ¼ sec. post at proper distance, from which
A Cedar 40" dia., bears N.20°W., 26 lks. dist.
A R.Fir 7" dia., bears S.10°E., 7 lks. dist.

GL0 survey by Fred Mensch, Contract #757 dated Sept. 14, 1904 (DCSO records, Vol. 15 Pages 6509-10)

The 1/4 Cor., being partially obliterated, I re-establish this corner in its original position, as follows:
Set a basalt stone 18x14x10 ins., 12" in the ground for ¼ sec. cor., mkd. ¼ on N. face; from which
A Cedar 40" dia., bears N.20°W., 26 lks. mkd. ¼ S31 BT.
A R.Fir 14" dia., bears S.20°E., 18 lks. mkd. ¼ S6 BT.

John H. Markham, Jr. - For: Stomar Lumber Co. - Aug/Sept 1956 C.S. File 42/191-2

Found - 44" Cedar bears N.20°W., 17.2 ft., 0.B.T., found scribe.
At corner point, found stone and Set truck axle with flange up, from which
12" W.Fir bears S.83°W., 36.0 ft. mkd. ¼ S6 BT.
20" W.Fir bears N.51°E., 24.7 ft. mkd. ¼ S BT.
Road bears N.30°E., 62.0 ft.

BLM resurvey by Wayne Rogers, under Contract #1030 - Surveyed Aug/Sept. 1980 (DCSO records, Vol. 45 Page 17255)

The 1/4 Cor., perpetuated and recorded by Markham in 1956, monumented with an axle, 1¼" dia., firmly set, projecting 20" above the ground, from which the remains of the original bearing tree:
A Cedar 53" dia., bears N.20°W., 26 lks. with scribe marks ¼ S31 BT visible on opened blaze. This tree was rescribed by Mensch in 1905.
and bearing tree by Markham:
A Grand Fir 30" dia., bears N.51°E., 38 lks. dist., with illegible scribe marks visible on partially healed double blaze.
A Grand Fir 19" dia., bears S.85°W., 53 lks. dist., with healed double blaze.

(Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 129100

PRIMARY CORNER DESCRIPTION No. 1/4 Sec. 6 only, T 30-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 29 S R 6 W
1/4 S 6
T 30 S R 6 W
1980

and a new bearing tree:

A Grand Fir 17" dia., bears S.68°E., 68 lks. dist., mkd.
¼ S6 BT.

Deposit the axle alongside the iron post.

DCS0-GIS Corner visitation - 8/10/2004 - Typed: 2/9/2011 -
C.S. File 67/33-1

Monument - 2.5" BC/IP
Comment - OK