

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 31

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM survey by Wayne L. Rogers, Cadastral Surveyor - under Group #1030, surveyed Aug/Sept. 1980 (DCSO records Vol. 45 Page(s) 17265-66)

Point for the center ¼ sec. cor. of sec. 31, at intersection with the E. and W. center line.

Set an iron post, 28" long 2½" dia., 24" in the ground, with brass cap mkd.

T 29 S R 6 W
C 1/4 S 31
1980

from which

A Fir 7" dia., bears S.30¼°E., 35½ lks. dist., mkd. C 1/4 S31 BT.

A Fir 5" dia., bears N.27½°W., 28½ lks. dist., mkd. C 1/4 S31 BT.

BLM Retracement by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2300, Surveyed Aug./Sept. 2009 - (DCSO records Vol. 56 Page(s) 22275-6 & Plat T29-6 2011)

The center ¼ sec. cor. of sec. 31, established by Rogers in 1980, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remaining bearing tree mkd. by Rogers

A fir, 14" dia., bears S.30¼°E., 23.4 ft., with a healed blaze.

and a new accessory

A rebar, 30" long, 5/8" dia., driven 28" in the ground for a reference monument, bears N.40°11'46"E., 15.06 ft. with an alum. cap mkd. RM C¼ S31 15.1 FT TO COR and on arrow pointing to the corner.

From this corner, a point established by person(s) unknown bears S.21°47'16"W., 2.98 ft., monumented with on iron pipe, 1" dia., firmly set, projecting 12" above ground, and was not utilized in the course of this survey.

Latitude 43°00'22.70"N. Longitude 123°26'53.2"W.
(NAD 1983 (CORs 96))