

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch under Contract #757 dated Sept. 14, 1904 (DCSO records Vol. 15 Page(s) 6497)

Set a diorite stone 12 x 10 x 8 ins., 8" in the ground for ¼ sec. cor., marked ¼ on N. face, from which
A Cedar 48" dia., bears N.1°W., 7 lks. marked ¼ S30 BT.
A Red Fir 16" dia., bears S.20°W., 32 lks. mkd. ¼ S31 BT.

Arthur Boyer - Wit: Frank Smith, D.B. Lewis, Mr. Hollenback -April 24, 1952 - C.S. File 41/24

Found - Original rock and witness trees. This cor. is on the side of a 28° slope facing West and about 250 ft. East of the bottom of the slope, it is very hard to find. All the trees have been burnt, although they are standing, mostly, and all are about the same size and height. Tacked an alum. tag on the Cedar witness tree which is in Sec. 30, tag is on the West face of the tree about 6 ft. above the ground.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell, Dale McFarland, crew - Feb. 1962 - C.S. 49/139-31

Found - Both orig. BTs, now snags. We open, now 22" Fir snag, S.20°W., 21.1 ft. and find good scribing "BT". We do not find corner stone.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 6 W
¼ $\frac{S\ 30}{S\ 31}$
1962
New BTs -4" Laurel bears S.17°E., 31.3 ft. scribed ¼ S31 CSBT
8" Laurel N.26°E., 103.0 ft. scribed ¼ S30 CS BT.

Fd. BC, 2 orig. BTs and 2 BTs by Byron, BLM survey by Wayne L. Rogers, under Group #1030, surveyed Aug/Sept. 1980 (DCSO records, Vol. 45 Pg. 17263

Ken Hoffine - For: Lone Rock Timberland Co - 12/2015 - M170-44

Found - Douglas Co. brass cap mkd: T29S R6W S30 S31 ¼ 1962
22" madrone bears S.16½°E., 31.2 ft. (rec. S.17°E., 31.3 ft) healed face.
D.Fir snag of indeterminate size bears S.20½°W., 21.1 ft. (rec. S.20°W., 21.12 ft) no visible face or scribe)

continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Cedar at record bearing, N.1°W., 4.62 ft., is now only root hole.
24" madrone bears N.23¼°E., 102.6 ft. (rec. N.24½°E., 100.98 ft. well healed face & tag.
17" D.Fir bears S.81¼°W., 18.5 ft. We scribed ¼ S31 BT & tag.
16" double madrone bears N.46¾°W., 21.7 ft. We scribe ¼ S30 BT & tag.
Corner lies on west slope approximately 100 ft. east of North South Creek 1.0 ft above ground level. Metal U-post and diorite stone beside.