

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 140240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Roger H. Gee - For: Western Land Mgt. Inc. - July 1970 - M 40-17

Set 5/8" Iron rod, from which
 A madrona 5" dia., bears S.83°47'W., 19.7 ft. scribed "C¼ S30 BT"
 A Chinquapin 10" dia., bears S.30°37'E., 27.9 ft. scribed "C¼ S30 BT"

Survey by Roger H. Gee - For: Western Land Mgt. Inc. - Nov. 1973 - M 52-25

Note: corner established in 1970 in error, destroyed by R.Gee

Set 5/8" Iron rod from which bears
 5" Madrone, S.86°07'W., 26.0 ft. scribed C¼ S30 BT.
 10" Chinquapin S.18°18'E., 24.9 ft. scribed C¼ S30 BT.

Ken Hoffine - For: Lone Rock Timberland Co - 12/2015 - M170-44

Found - 5/8" iron rod as per M52-25
 6" madrone bears S.86¼°W., 26.1 ft (rec. S.86°07'W., 26.0 ft.) visible scribing. We tag.
 12" chinquapin bears S.19¼°E., 23.4 ft. (Rec. S.18°18'E., 24.9 ft.) visible scribing. We tag.
New - 16" D.Fir bears N.83°W., 32.2 ft. We scribe C¼ S30 BT & tag.
 14" D.Fir bears N.24¾°E., 14.3 ft. We scribe C¼ S30 BT & tag.
Corner lies on steep north slope 0.5 ft. above ground level.