

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 19 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6483)

-----  
Set ¼ sec. post, at proper distance, from which  
A B.Oak 24" dia., bears S.28°W., 30 lks. dist.  
A B.Oak 10" dia., bears N.33°E., 44 lks. dist.

GL0 survey by Fred Mensch under Contract #757 dated Sept. 14, 1904 (DCSO records Vol. 15 Page(s) 6513)

-----  
Re-establish the ¼ sec. cor. as follows:  
Set an ironstone 12x8x6 ins., 8" in the ground for ¼ sec. cor. marked ¼ on N. face, from which  
A Laurel 12" dia., bears N.72°E., 26 lks. marked ¼ S19 BT.  
A Laurel 30" dia., bears S.3°E., 33 lks. marked ¼ S30 BT.

F.C. Frear - March 9, 1917 - Field Book 44 Pg. 27 (and "old" corner book, pg. 194)

-----  
Large rock set by new govt. survey, from which  
A Madrone 30" dia., bears S.4°E., 32 lks.  
A Madrone 12" dia., bears N.72¼°E., 25½ lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland, John Powell-crew - April 1962 - C.S. 49/139-33

-----  
Found - Stone, broken in several pieces, with scribed Fir guard stake at corner.  
NE Madrone has been cut down, found scribing on same "¼".

SE Madrone still standing, but rotted out on S. side  
Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 6 W  
¼  $\frac{S\ 19}{S\ 30}$   
1962

New BTs -12" Fir S.30°W., 49.0 ft. mkd. ¼ S30 CS BT.  
16" Laurel N.80°E., 50.5 ft. mkd. ¼ S19 CS BT.

Fd. OK, Howard Johnstone, Dec. 1989, M 101-73

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22728-9)

-----  
The ¼ sec cor. of secs 19 & 30, perpetuated by Byron in 1962 monumented with an iron post, 1¼" dia. firmly set, projecting 15" above ground (alongside of which is a portion .. cont.

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 19 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

... of Mensch's basalt stone 9x6x5" (Record 12x8x6"), loosely set with an incomplete 4 mark visible on a face) with brass cap (properly) mkd  
from which the remains of bearing trees mkd. by Mensch  
    A roothole bears N.72°E., 17.2 ft.  
    A madrone, 39" dia., bears S.30°E., 21.8 ft. with no marks visible.  
and the remains of bearing trees mkd. by Byron  
    A madrone, 22" dia., bears N.78¾°E., 50.2 ft., with a healed blaze.  
    A fir snag, 20" dia., bears S.29¾°W., 49.4 ft., with a healed blaze.  
Bury remains of Mensch's basalt stone alongside the iron post.