

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6485)

-----

Set 1/4 sec. post at proper dist., from which  
 A Laurel 12" dia., bears N.43°W., 60 lks. dist.  
 A Laurel 14" dia., bears S.71°W., 80 lks. dist.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12832)

-----

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
 Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked

	S 18
1/4	S 19
T 29 S R 6 W	
	1958

from which  
 A Fir 5" dia., bears N.53°W., 12 lks. dist. mkd. 1/4 S18 BT.  
 A Fir 5" dia., bears S.5 1/2°E., 4 lks. dist., mkd. 1/4 S19 BT.

Survey by Howard Johnstone, L.S. #498 - For: Roseburg Forest Products Co. - Dec. 1989 - M 101-73

-----

Set a 5/8" Iron rod and alum. cap.  
 New BTs -16" Maple bears N.45°W., 3.5 ft. scribed 1/4 S18 BT.  
 13" Fir bears N.89°E., 26.7 ft. scribed 1/4 S18 BT.  
 20" Fir bears S.14°E., 36.5 ft. scribed 1/4 S19 BT.  
 9" Fir bears S.13°W., 28.7 ft. scribed 1/4 S19 BT.  
 1958 Cadastral BC/IP bears N.89°16'25"W., 43.61 ft.

BLM Resurvey by Wayne L. Rogers and Bryan S. Seibold, Cadastral Surveyors, under Group #1517, surveyed April/Aug. 1990 - (DCSO records Vol. 50 Page(s) 19174-75)

-----

The 1/4 sec. cor. reestablished by proportionate measurement and recorded by Johnstone, in 1989; there is no remaining evidence of the original corner, therefore, this position is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above ground, with aluminum cap, 2 ins. diam., mkd.

T 29 S RRCO R 6 W
1/4 S
S 18
S 19
1989
LS 498

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which bearing trees mkd. by Johnstone  
A fir, 12 ins. diam., bears N. 89° E., 39 lks. dist., with scribe marks 1/4 S18 BT visible on open blaze.  
A fir, 25 ins. diam., bears S. 14° E., 55 lks. dist., with scribe marks 1/4 S19 BT visible on open blaze.  
A fir, 9 ins. diam., bears S. 13° W., 44 lks. dist., with scribe marks 1/4 S19 BT visible on open blaze.  
A maple, 17 ins. diam., bears N. 45° W., 5 lks. dist., with scribe marks 1/4 S18 BT visible on open blaze.

From this point, the ¼ sec. cor. of secs. 18 and 19 erroneously reestablished by Thielsen and White in 1958-59, bears N. 89° 25' 00" W., 0.660 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S18 S19 T29S R6W 1958, from which bearing tree mkd. by Thielsen and White:  
A fir, 11 ins. diam., bears S. 5½° E., 4 lks. dist., with healed blaze.  
A fir, 9 ins. diam., bears N. 53° W., 12 lks. dist., with healed blaze.

The iron post was removed and the marks on the bearing trees were obliterated.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22731)

-----  
The ¼ sec. cor. of secs. 18 and 19, monumented with a threaded iron rod, 5/8" dia., firmly set, projecting 11" above ground, with an aluminum cap (properly) mkd, from which bearing trees mkd. by Johnstone, in 1989  
A fir, 15" dia., bears N.86°E., 25.7 ft., with a healed blaze. (Record, N.89°E.)  
A fir, 30" dia., bears S.14°E., 36.3 ft., with a healed blaze.  
A fir, 13" dia., bears S.10¾°W., 29.0 ft., with a healed blaze. (Record, S.13°W.)  
A maple, 18" dia., bears N.45°W., 3.3 ft., with a healed blaze.

Corner is located on an E. slope.