

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6486)

Set ¼ sec. post at proper dist., from which
A W.Oak 12" dia., bears N.11½°E., 59 lks. dist.
A B.Oak 12" dia., bears S.70°W., 145 lks. dist.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12836)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with brass cap mkd:
¼ $\frac{S\ 7}{S\ 18}$
T 29 S R 6 W
1958

from which
A Fir 14" dia., bears N.27°W., 161 lks., mkd. ¼ S7 BT.
A Hemlock 18" dia., bears S.58°W., 82 lks., mkd. ¼ S18 BT.

BLM resurvey by Robert Chappel, under Group #1616, surveyed June/Sept. 1991 (DCSO records Vol. 50 Page(s) 18895)

From the ¼ sec. cor. of secs. 7 and 18, determined at record bearing and distance from the remaining bearing tree mkd. by Thielsen and White in 1958:

A fir, 24 ins. diam., bears N. 27° W., 161 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T29S R6W
¼ $\frac{S\ 7}{S\ 18}$
1991

from which a new bearing tree

A fir, 12 ins. diam., bears N. 85½° E., 87 lks. dist., mkd. X BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

Greg Lang - For: Roseburg Resources Co. - 1/2016 - M170-41

Found - Brass cap
24" D.Fir, bears N.86°E., 57.42'
28" D.Fir bears N.26½°W., 106.26' continued next pg

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New -	11" D.Fir bears S.36½°E., 69.15', scribed "¼ S18 BT"
	12" Maple bears S.60½°W., 65.20', scribed "¼ S18 BT"