

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 140540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 7

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

BLM resurvey by Robert Chappel, under Group #1616, surveyed June/Sept. 1991 (DCSO records Vol. 50 Page(s) 18904)

-----  
Point for the center ¼ sec. cor. of sec. 7, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

T29S R6W  
C¼ S 7  
1991

from which

A fir, 6 ins. diam., bears S. 73¼° E., 24 lks. dist., mkd. X BT on double blaze.

A fir, 16 ins. diam., bears S. 83 3/4° W., 23 lks. dist., mkd. C¼ S7 BT.

Deposit a white "DEEP-1" magnetic marker at base and set steel fence post alongside the stainless steel post.

From this point, a point unofficially established as the C¼ sec. cor. by the Bureau of Land Management during an administrative survey in 1960, bears S. 50° 11' 30" E., 0.120 chs. dist.; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 6 ins. above ground.