

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6488)</p> <p>-----</p> <p>Set ¼ sec. post at proper dist., from which A B.Oak 8" dia., bears N.18½°E., 40 lks. dist. A Laurel 8" dia., bears S.38°W., 13 lks. dist.</p>
<p>Survey by G.G. Stewart - Wit: Geo. Keller; Chas. Voytiela; Jesse Davenport - For: Chas. Voytilla - Dec. 8, 1921 - C.S. File 34/13; C.S. 6/18; Vol. 3 Pg. 96 & "old" Cor. book, Pg. 131</p> <p>-----</p> <p>Stake set in ground in 1906 by Brown, D.C.S. No notes for witness trees. Reset Corner. Iron Pipe from which A 8" Fir N.29°W., 28.0 ft. A 14" Maple S.15°W., 43.0 ft. Corner is 2921.1 ft. from East section and 3130.8 ft. from West corner.</p>
<p>Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12840)</p> <p>-----</p> <p>Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with brass cap mkd: ¼ $\frac{S\ 6}{S\ 7}$ T 29 S R 6 W 1958</p> <p>from which A Fir 14" dia., bears N.6°W., 40 lks. dist. mkd. ¼ S6 BT. A Chinquapin, 6" dia., bears S.28°W., 26 lks. dist., mkd. ¼ S7 BT.</p>
<p>Corner Fd. OK, BLM survey by Robert J. Chappel under Group #1616, Surveyed, June/Sept. 1991 (DCSO records Vol. 50 Page(s) 18898-99)</p>
<p>Fd. OK by Donald Bentz, May 1992 , M 115-35</p>