TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 160200

PRIMARY CORNER DESCRIPTION E. 1/16 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Arthur Boyer - Wit: Frank Smith, D.B. Lewis, Mr. Hollenback -April 24, 1952 - C.S. File 41/24

Set a steel jeep axle with flange on top. This corner is on a flat about 15 ft. above and 75 ft. E. about, from a through road which is surfaced. There is a fir tree 18" dia., with a board nailed on it which was previously taken for this corner. It is about 40 ft. N.45°W., from the true corner of this forty.

BLM survey by Wayne L. Rogers, under Group #1030, surveyed Aug/Sept. 1980 - (DCSO records Vol. 45 Page(s) 17262)

Point for the E 1/16 sec. cor. of secs. 30 and 31.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked E 1/16 S 30 / S 31 / 1980

from which
A Fir 15" dia., bears S.55°E., 23½ lks. dist., mkd. E 1/16 S31 BT.
A triple Yew 11" dia., bears N.20½°W., 48 lks. dist., mkd. E 1/16 S30 BT.