

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 160320

PRIMARY CORNER DESCRIPTION SE 1/16 Cor. Sec. 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - F.C. Frear, Deputy - 3/1918
(Added 8/25/2022) Old Vol. 3 Pg 39 (FB 44 P23)

Set a 4 yew stake from which
A 30" Fir bears S.65¼°W., 31 lks.
A 12" Maple bears N.49°E., 37 lks.

James W. Byron, Dep. Co. Surveyor - Dale McFarland and John Powell - Apr 1962 (added 8/25/2022) - C.S. 49/139-37

Found - Scribed stake at cor. 8' West of road & on EW fence line. We find:
36" R.Fir bears S.68°W., 22.0' bark scribed CS 1/16S. This BT now dead.
Set - 3/4" I.R. alongside scribed stake for 1/16 cor.
New BT - 8" R.Fir bears N.51°W., 28.6 scribed 1/16 S 19 CSBT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 (added 8/25/2022)- (DCSO records Vol. 57 Page(s) 22735)

The SE 1/16 sec. cor. of sec. 19, established by Freer, Deputy County Surveyor, in 1918. perpetuated by person(s) unknown, and is accepted as the cor., monumented with a rebar. 5/8" dia., firmly set, projecting 6" above ground, from which the remains of a BT mkd. by Freer
A sawed, decayed fir stump, 37" dia., bears S.68°W., 21.8 ft., with no marks visible.
At the corner point
Place an aluminum cap on the existing rebar, mkd.
SE 1/16 S 19
2009
from which new bearing trees
A fir, 15" dia., bears S.39½°W., 27.8 ft., mkd. SE 1/16 S19 BT.
A fir, 16" dia., bears N.75°W., 14.6 ft. mkd. X BT.
Corner is located W., 10 ft. from a gravel road, 12 ft. wide, bears N.30°W. and S.30°E., alongside a gate post.