

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch under Contract #757 dated Sept. 14, 1904 (DCSO records Vol. 15 Page(s) 6495)

Set an ironstone 15 x 12 x 8 ins., 10" in the ground for cor. of sec. 29, 30, 31 and 32, marked with 1 notch on S. and 5 notches on E. edge, from which

A Red Fir 12" dia., bears N.72°E., 27 lks. dist., marked T29S R6W S29 BT.

A Red Fir 16" dia., bears S.42°E., 7 lks. dist., marked T29S R6W S32 BT.

A Red Fir 12" dia., bears S.86°W., 11 lks. dist., marked T29S R6W S31 BT.

A Laurel 14" dia., bears N.32°W., 34 lks. dist., marked T29S R6W S30 BT.

Arthur Boyer - Wit: Frank Smith, D.B. Lewis, Mr. Hollenback - April 23, 1952 - C.S. File 41/24

Found the SE corner of sec. 30, the orig. rock and wit. trees which are on a flat about 100 ft. South of a flowing stream and about N.45°W., 75 ft. from the site of a homesteader's cabin in sec. 32.

Survey by John Markham, Jr. - For: Stomar Lumber Co. - Aug/Oct. 1956 - C.S. File 42/190-4

Found - 23" Fir S.42°E., 4.6 ft. - 0.B.T. - rescribed.

24" Fir N.72°E., 18.0 ft. - 0.B.T. - rescribed.

14" Fir S.87°W., 8.0 ft. - 0.B.T. - rescribed.

10" Laurel N.33°W., 23.2 ft. - 0.B.T. - dead.

At point for corner found stone and set 3/4" x 30" Iron pipe, from which

24" Laurel bears N.23°W., 35.5 ft. mkd. S30 T29S R6W 2880 BT.

20" Laurel bears S.12°W., 23.7 ft. mkd. S31 T29S R6W W.M. BT.

BLM resurvey by Wayne L. Rogers, under Group #1030, surveyed Aug/Sept. 1980 - (DCSO records Vol. 45 Page(s) 17261-62)

The sec. cor. perpetuated and recorded by Markham in 1956, monumented with an iron pipe 1" dia., firmly set, projecting 6" above ground, alongside of which is the original basalt stone, 15 x 12 x 8 ins., firmly set, projecting 6" above ground with 5 notches on E. and 1 notch on S. edges, from which the remains of the original bearing trees

A Fir snag 23" dia., bears N.72°E., 27 lks. dist., with healed blaze. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

A Fir snag 21" dia., bears S.42°E., 7 lks. dist., with healed blaze.
 A Fir snag 15" dia., bears S.86°W., 11 lks. dist., with illegible scribe marks visible on opened blaze.
 and bearing trees mkd. by Markham
 A Madrone 25" dia., bears S.12°W., 36 lks. dist., with scribe marks S31 T29S R6W visible on bark.
 A Madrone snag 20" dia., bears N.23°W., 53 lks. dist., with scribe marks S30 T29S R6W 2880 visible on bark.
 At the corner point
 Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 29 S	R 6 W
S 30	S 29
S 31	S 32

1980

from which new bearing trees
 A Fir 13" dia., bears N.20½°E., 29 lks. dist., mkd. T29S R6W S29 BT.
 A Cedar 7" dia., bears S.69°E., 39 lks. dist., mkd. T29S R6W S32 BT.
 A Cedar 15" dia., bears S.29°W., 15 lks. dist., mkd. T29S R6W S31 BT.
 A Cedar 16" dia., bears N.73½°W., 24½ lks. dist., mkd. T29S R6W S30 BT.
 Deposit the stone and the iron pipe alongside the iron post.

BLM Retracement by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2300, Surveyed Aug./Sept. 2009 - (DCS0 records Vol. 56 Page(s) 22275-6 & Plat T29-6 2011)

The cor. of secs. 29, 30, 31, & 32, established by Mensch in 1905, perpetuated by Markham, in 1956, subsequently perpetuated by Rogers in 1980, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, (alongside of which is the orig. basalt stone, 15x2x8", loosely set, projecting 9" above ground, with 5 notches on SE. edge and 1 notch on SW. edge) with brass cap (properly) mkd. from which the remains of the orig. BTs
 A sawed, decayed fir stump, 26" dia., bears N.72°E., 17.8 ft., with no marks visible.
 A decayed fir stump, size indeterminate, bears S.42°E., 4.6 ft., with no marks visible.
 A sawed fir stump, 5 ft. tall, 12" dia., bears S.86°W., 7.3 ft., with a healed blaze.
 and the remains of BTs mkd. by Markham, reported by Rogers
 A sawed, decayed madrone stump, size indeterminate, bears S.12°W., 23.8 ft., with no marks visible.
 continued next page

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A sawed, decayed madrone stump, size indeterminate, bears N.23°W., 35.0 ft., with no marks visible.
and the remains of bearing trees mkd. by Rogers
A sawed fir stump, 5 ft. high, (6" dia., bears N.20½°E., 19.1 ft., with a healed blaze.
A sawed cedar stump, 6 ft. high, 22" dia., bears S.29°W., 9.9 ft., with a healed blaze.
A sawed cedar stump, 6 ft. high, 21" dia., bears N.73½°W., 16.2 ft., with a healed blaze.
and new bearing trees
A cedar, 11" dia., bears N.61¼°E., 44.5 ft., mkd. T29S R6W S29 BT.
A cedar, 10" dia., bears S.28¾°E., 16.0 ft., mkd. T29S R6W S32 BT.
A cedar, 22" dia., bears S.54°W., 91.1 ft., mkd. T29S R6W S31 BT.
A cedar, 10" dia., bears N.57°W., 48.9 ft., mkd. T29S R6W S30 BT.
Bury the orig. stone alongside the iron post.
Latitude 43°00'48.717"N. Longitude 123°26'35.363"W.
(NAD 1983 (CORS 96))

Ken Hoffine - For: Lone Rock Timberland Co - 12/2015 - M170-44

Found - BLM brass cap marked T29S R6W S29 S30 S31 S32 1980.
13" I.Cedar bears S.29¼°E., 16.8 ft <rec S.28¾°E., 16.0 ft>. Healed face and tag.
22"x6 ft I.Cedar stump bears S.29°W., 9.9 ft <rec S.29°W., 9.9 ft>. Healed face and tag.
Stump hole bears S.88½°W., 7.2 ft <rec S.86°W., 7.3 ft> Rotten stump beside. Place mag hub at center.
21"x6 ft I.Cedar stump bears N.73½°W., 16.3 ft <rec N.73½°W., 16.2 ft>. Healed face and tag.
12"x5 ft D.Fir stump bears N.21°E., 19.1 ft <rec N.21°E., 19.1 ft>. Healed face and tag.
12" I.Cedar bears N.57°W., 48.5 ft <rec. N.57°W., 48.9 ft>. Partially healed face and tag.
13" I.Cedar BT <rec N.61¼°E 44.5 ft> Found in good condition with tag and partially healed face.
24" I.Cedar BT <rec S.54°W., 91.1 ft> Found in good condition with tag and partially healed face.
24"x1 ft D.Fir stump BT <rec N.72°E., 17.8 ft> Found partially rotted with no tag or visible scribing.
A D.Fir stump of indeterminate size at <rec S.42°E., 4.6 ft>.
A Madrone stump of indeterminate size fd badly deteriorated at <rec S.12°W., 23.8 ft>. No tag or scribing visible. continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

A madrone stump of indeterminate size found badly deteriorated at <record N.23°W., 35.0 ft>. No tag or scribing visible corner lies on flat approx. 100 ft West of rock road 0.3 ft above ground level. Metal T-post beside.