

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch under Contract #757 dated Sept. 14, 1904 (DCSO records Vol. 15 Page(s) 6495)

A Willow, 5" dia., for ¼ sec. cor. I mark ¼ S30 on W. and 29 on E. side, from which
 A Laurel 12" dia., bears N.77°E., 27 lks. dist., mkd. ¼ S29 BT.
 A Laurel 7" dia., bears S.63°W., 25 lks. mkd. ¼ S30 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell, Dale McFarland, crew - Feb. 1962 - C.S. 49/139-31

Found - Orig. 7" now 14" Laurel S.63°W., 16.5 ft. We open and find good scribing "BT"
 Orig. 12" now 20" Laurel N.77°E., 17.8 ft. shows good scars.
Corner lies in center of logging road. We drive 3/4" Iron rod at corner and flush with road surface.
New BT - 14" Red Fir bears N.71°W., 26.4 ft. scribed ¼ S30 CS BT.

Fd. OK, by Burton Holt, March 1987, M 104-3

Ken Hoffine - For: Lone Rock Timberland Co - 12/2015 - M170-44

Found - 3/4" iron rod.
 13" I.Cedar bears S.59¼°E., 40.8 ft. We scribe ¼ S29 BT and tag.
 23" madrone bears N.76°E., 18.1 ft. (Rec N.77°E., 17.8 ft). Partially healed face and tag.
 15" Madrone bears S.62½°W., 16.6 ft. (Rec S.63°W., 16.5 ft). Partially healed face and tag.
 21"x5 ft D.Fir stump bears N.71½°W., 26.6 ft (rec N.71°W., 26.4 ft). Healed face and tag.
Corner lies in middle of rock road running N.20°E., near old gate and East West running fence 0.1 ft below ground level.