

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6482)

-----  
Set post, cor. of secs. 19, 20, 29 and 30, from which  
A Cedar 40" dia., bears S.48°W., 36 lks  
A Red Fir 24" dia., bears N.23°W., 44 lks. dist.  
A Red Fir 12" dia., bears N.43°E., 80 lks. dist.  
A B.Oak 20" dia., bears S.30°E., 38 lks. dist.

GLO survey by Fred Mensch under Contract #757 dated Sept. 14, 1904 (DCSO records Vol. 15 Page(s) 6511)

-----  
Found no trace of post or trees.  
I re-establish the cor. of secs. 19, 20, 29 and 30, as follows  
Set a sandstone 15x8x8 ins., 10" in the ground for cor. mkd. with 2 notches on S. and 5 notches on E. edge, from which  
A Red Fir 24" dia., bears N.24°E., 19 lks. dist., mkd. T29S R6W S20 BT.  
A Red Fir 18" dia., bears S.31°E., 68 lks. dist., mkd. T29S R6W S29 BT.  
A Red Fir 12" dia., bears S.20°W., 50 lks. dist., mkd. T29S R6W S30 BT.  
A Laurel 20" dia., bears N.77°W., 59 lks. dist., mkd. T29S R6W S19 BT.

F.C. Frear - March 9, 1917 - Vol. 3 Pg. 39; (and "old" corner book, Pg. 194)

-----  
Large rock set by new govt. survey, from which  
A Madrone 18" dia., bears N.76½°W., 58 lks.  
A Fir 18" dia., bears S.31°E., 62½ lks.  
A Fir 12" dia., bears S.20 3/4°W., 49 lks.  
A Fir 24" dia., bears N.19½°E., 17 lks.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12828-29)

-----  
The sec. cor., determined at record bearing and distance from the bearing trees mkd. by Mensch in 1904. This cor. was established by Ford in 1854, and reestablished by Mensch, from which  
A rotted Fir stump 30" dia., bears N.24°E., 19 lks. dist., no marks remain.  
A Fir 24" dia., bears S.31°E., 68 lks. dist., mkd. with healed blaze.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Fir 18" dia., bears S.20°W., 50 lks. dist., mkd. with healed blaze.

A Madrona snag 24" dia., bears N.77°W., 59 lks. dist., mkd. T29S R6W S19 BT.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked

T 29	S R 6 W
<u>S 19</u>	<u>S 20</u>
S 30	S 29
1958	

from which new bearing trees:

A Fir 10" dia., bears N.22 3/4°E., 37 lks. dist., mkd. T29S R6W S20 BT.

A Fir 12" dia., bears N.22½°W., 91 lks. dist., mkd. T29S R6W S19 BT.

Fd. OK, Howard Johnstone, Dec. 1989, M 101-73

BLM resurvey by Wayne L. Rogers and Bryan S. Seibold, Cadastral Surveyors, under Group #1517, surveyed April/Aug. 1990 - (DCSO records Vol. 50 Page(s) 19166)

The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 29	S R 6 W
<u>S 19</u>	<u>S 20</u>
S 30	S 29
1958	

from which the remains of original bearing trees

A fir root crown, size indeterminate, bears N. 24° E., 19 lks. dist., no marks visible.

A sawed fir stump, 24 ins. diam., bears S. 31° E., 63 lks. dist., with healed blaze. (Record, 68 lks.)

A fir, 26 ins. diam., bears S. 20° W., 50 lks. dist., with healed blaze.

A madrone root crown, size indeterminate, bears N. 77° W., 59 lks. dist., no marks visible.

and the bearing trees mkd. by Thielsen and White

A fir, 19 ins. diam., bears N. 22 3/4° E., 37 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears N. 22½° W., 91 lks. dist., with healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears S. 13° E., 21½ lks. dist., mkd. T29S R6W S29 BT.

The cor. is located in the cor. of fences extending E, W, N

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed April/June 2002, - (DCSO records Vol. 54 Page(s) 21134-5)

The cor. of secs. 19, 20, 29, & 30, monumented with an iron post, 2½" dia., firmly set, projecting 4 ins. above ground, with brass cap (properly) mkd.

from which the remains of bearing trees by Mensch

A decayed fir stump, size indeterminate, bears N.20½°E., 11.8 ft., with no marks visible. (Record, N.24°E., 12.5 ft.)

A sawed fir stump, 25" dia., bears S.31°E., 41.6 ft., with a healed blaze.

A fir, 28" dia., bears S.20°W., 33.0 ft., with a healed blaze.

and the remains of bearing trees mkd. by Thielsen and White

A sawed fir stump, 26" dia., bears N.22¾°E., 24.4 ft., with a healed blaze.

A fir, 25" dia., bears N.22½°W., 60.1 ft., with a healed blaze.

and a bearing tree mkd. by Rogers and Seibold

A fir, 11" dia., bears S.13°E., 14.2 ft., with a healed blaze.

and a new bearing tree

A cedar, 6" dia., bears N.25°E., 38.7 ft. mkd. X BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Corner is located 2.7 ft. west of the cor. of un-maintained woven wire fences, extending North, East, and West.

The geographic position (NAD 1983) of this cor. as determined by a differentially corrected, mapping grade GPS receiver (Trimble Geo Explorer 3), observation, is as follows:

Latitude: 43°01'40.96"N. Longitude: 123°26'35.03"W.

DCSO-GIS Corner visitation - 8/20/2004 - Typed: 2/1/2011 - C.S. File 67/33-1

Monument - GLO/BLM 2.5" BC/IP

Comment - ok

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22727-8)

The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd. continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of bearing trees mkd. by Mensch  
A decayed fir stump, size indeterminate, bears N.20½°E.,  
11.8 ft., with no marks visible.  
A sawed fir stump, 24" dia., bears S.31°E., 41.6 ft., with  
a healed blaze.  
A fir, 29" dia., bears S.20°W., 33.0 ft., with a healed  
blaze.  
and the remains of bearing trees mkd. by Thielsen and White  
A sawed fir stump, 26" dia., bears N.22¾°E., 24.4 ft.,  
with a healed blaze.  
A fir, 30" dia., bears N.22½°W., 60.1 ft., with a healed  
blaze.  
and a bearing tree mkd. by Rogers and Seibold  
A fir, 13" dia., bears S.13°E., 13.8 ft., with a healed  
blaze. (Record, 14.2 ft.)  
and a bearing tree mkd. by Moore and Browning  
A cedar 10" dia. bears N.25°E., 38.7 ft. with a healed  
double blaze.  
Corner is located W 2.5 ft. from the cor. of broken down  
barbed and woven wire fences extending N, E, & W on a N  
slope.