

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6485)

Set ¼ sec. post, from which
 A Laurel 16" dia., bears N.27°E., 60 lks. dist.
 A Laurel 20" dia., bears S.6½°W., 44 lks. dist.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12833-34)

The ¼ sec. cor. determined at record bearing and distance from the remaining original bearing tree:
 A Madrona 30" dia., bears S.6½°W., 44 lks. dist., mkd. ¼ S BT on open blaze.

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked ¼

S 18 S 17
T 29 S R 6 W
1958

from which new bearing trees:
 A Fir 14" dia., bears S.24½°E., 44 lks. dist., mkd. ¼ S17 BT.
 A Fir 12" dia., bears N.50°W., 59 lks. dist., mkd. ¼ S18 BT.

Fd. OK by Howard Johnstone Dec. 1989 - M 101-72

Fd. OK, in BLM resurvey by Rogers and Seibold, Cadastral Surveyors, under Group #1517, surveyed April/Aug. 1990 - (DCSO records, Vol. 50 Page 19177)