

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6485)

Set post, cor. secs. 7, 8, 17 and 18, from which
A Laurel 18" dia., bears S.17°W., 16 lks. dist.
A Laurel 18" dia., bears N.88°E., 79 lks. dist.
A Laurel 16" dia., bears N.58°W., 27 lks. dist.
A B.Oak 12" dia., bears S.49°E., 25 lks. dist.

Survey by Gene E. Johnson - For: Clyde Johnson - Nov. 23, 1953 - C.S. File 41/248-2

Found - O.B.T., 24" Madrone bears S.17°E., 10.6 ft. (Rec. S.17°W., 10.6 ft.)
Stump of old Madrone BT, bears N.88°E., 52.1 ft.
Found old decayed scribed post near corner point.
At corner point Set 4" x 4" x 30" Fir stake blazed and scribed, from which
New BTs - 12" Fir N.75°W., 10.0 ft.
8" Fir S.27°W., 29.5 ft.
6" Fir N.40°E., 54.5 ft.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12834)

The Sec. cor., determined at record bearing and distance from the remaining original bearing tree:
A Madrona 30" dia., bears S.17°W., 16 lks. dist., mkd. BT on bark, with open and rotted blaze.

At the corner point
Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with brass cap mkd:

	T	29	S	R	6	W
		S	7		S	8
		S	18		S	17
						1958

from which new bearing trees:
A Fir 10" dia., bears N.12°E., 82 lks. mkd. T29S R6W S8 BT
A Fir 8" dia. bears S.66°E., 100 lks. mkd. T29S R6W S17 BT
A Fir 12" dia. bears S.78°W., 50 lks. mkd. T29S R6W S18 BT
A Fir 8" dia., bears N.83°W., 84 lks. mkd. T29S R6W S7 BT.

Fd. OK, Eugene Bloom, April 1983, C.S. File 58/242 - 2
Fd brass cap, Mark Heimburger, 2/2007 - M148-58

Greg Lang - For: Roseburg Resources Co. - 1/2016 - M170-41

Found - Brass cap continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New -	30" Madrone bears [S.17°W., 10.56'] BLM rec. 26" D.Fir bears [S.78°W., 33.0'] BLM rec. 22" D.Fir bears [S.66°E., 66.0'] BLM (61.2) CS58/242-2 14½" D.Fir bears N.38¼°W., 7.60', scribed "T29S R6W S7 BT" 6½" W.Fir bears N.39¼°E., 27.90', scribed "T29S R6W S8 BT"
-------	---