TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6487)

Set ¼ sec. post, from which
A W.Oak 8" dia., bears S.18°W., 17 lks. dist.
A W.Oak 8" dia., bears N.30°E., 12 lks. dist.

Survey by Gene E. Johnson - For: Clyde Johnson - Feb. 23, 1953 - C.S. File 41/248-1

At cor. point I find an old scribed post lying in fence line and hole in ground containing oak roots, which Harrison Rice swears is the position of the bearing tree for sec. 7, which was a dead 14" Oak, and was destroyed in process of building fence, bears S.18°W., 17 lks. from cor. point.
At cor. point, Set 3/4" x 30" Galv. I.P. with 4" x 4" x 36" scribed Fir stake alongside, from which
New BTs -12" Fir bears S.69°E., 38.0 ft.
14" Fir bears S.72½°W., 25.5 ft.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12837-38)

The ¼ sec. cor., perpetuated with an iron pipe 3/4" dia., 6" above ground, firmly set. The Douglas County records show that this pipe was set by Gene Johnson, R.E. #3561, in 1953, from evidence of the original survey and from sworn testimony of Harrison Rice, a local resident, who had knowledge of the cor. position. This point is accepted as the best available evidence of the original cor. position.
At the corner point
Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with brass cap mkd:

```
        ¼
     S 7 | S 8
S 29 S | R 6 W
      1958
```

from which trees marked by Johnson:
A Fir snag 12" dia., bears S.69°E., 57 lks. dist., mkd. ¼ S RE3561 BT on open blaze.
A Fir 14" dia., bears S.72½°W., 38 lks. dist., mkd. ¼ S RE3561 BT on open blaze.
and a new bearing tree:
A Fir 8" dia., bears N.7°E., 101 lks. dist., mkd. ¼ S8 BT.

Fd. OK, by Eugene Bloom, April 1983, C.S. File 58/242-2

(Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Cor. Fd. OK, by BLM resurvey by Robert Chappel, under Group #1616, surveyed June/Sept. 1991. (DCSO records, Vol. 50 Pg.18896)

Fd brass cap, Mark Heimburger, 2/2007 - M148-58