

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6488)

Set ¼ sec. post, at proper dist., from which
A B.Oak 10" dia., bears N.22°E., 4 lks. dist.
A B.Oak 12" dia., bears N.30°W., 72 lks. dist.

J. W. Springer - Wit: C. Sherrill; John Prowell; Otto Parker; Ray Powell; J.D. and Edgar Walker - Mar. 31, 1923 - Vol. 3 Pg. 140, C.S. File 34/13 and Field Book 60 Pgs 87-88 (and "old" corner book, pg. 132)

Replaced corner from original BTs, one in bad shape and other one fair. Drove an Iron pipe 1½" x 40" in ground and marked two new BTs
A Fir 12" dia., N.59°40'W., 26.6 ft.
B.Oak 10" dia., N.24°00'E., 27.3 ft.
Both original BTs are in evidence at the time.

Survey by Marvin C. Ramsey - For: J.H. Baxter Co. - March 27 to May 23, 1963 - C.S. File 51/258 and M 26-8

Determined by the only extant orig. BT:
24" B.Oak bears N.30°W., 72 lks. dist. with negative scribe marks ¼ S.
The I.P. and BTs by Springer dated 1923 have been destroyed by a logging operation.
Set Iron pipe 3 ft. long 1½" dia., 28" in the ground marked RS404, from which
18" D.Fir bears N.62°E., 95 lks. mkd. ¼ S5 RS404 BT.
10" D.Fir bears N.89°W., 50 lks. mkd. ¼ S6 RS404 BT.

Douglas Co. Surveyors Office - Clell Goodwin, Gary L. Langlitz, Deputies, M. Lenora Ladig, A. Vic. Cangie, crew - Oct. 21, 1975 - C.S. File 57/36-20

Found - Iron pipe 3 ft. long, 1½" dia., 28" in ground, mkd: RS404, from which
An orig. 12" now 24" B.Oak bears N.30°W., 47.5 ft.
An orig. 18" now 20" Fir bears N.62°E., 62.7 ft.
New BT - 10" Fir bears S.65°W., 78.3 ft. scribed "¼ S6 CS BT" in double blaze.

BLM Resurvey, by Dale B. Bedell, Surveyed under Group No. 1714. Surveyed July - October 1994. (D.C.S.O. records Vol. 52 Page(s)19673)

Cont. Next page

TOWNSHIP 29 RANGE 6 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Beginning at the 1/4 sec. cor. of secs. 5 and 6, perpetuated by Springer in 1923, relocated and perpetuated by Ramsey, 1963, and further perpetuated by Langlitz, D.County Surveyor, in 1975 (as recorded in Douglas County Surveyor's Office corner renewal record, T. 29 S., R. 6 W., No. 229); monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 3 ins. above the ground, with a brass disk mkd. RS 404, from which the remaining original bearing tree:

A black oak, 29 ins. diam., bears N.30°W., 72 lks. dist., with healed blaze.

and a bearing tree mkd. by Ramsey

A fir, 22 ins. diam., bears N.64½°E., 94½ lks. dist., with healed blaze.

and a bearing tree mkd. by Langlitz

A fir, 18 ins. diam., bears S.68°W., 120 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T29S R6W

1/4

S 6 | S 5

1994

Deposit iron pipe alongside and white "DEEP-1" magnetic marker at the base of the stainless steel post.

The corner is located 0.03 chs. W. of the corner of fences extending N., S., and E.

From this point, National Geodetic Survey triangulation station "TWO OAKS" 1942, bears S.89°17'12"W., 138.024 chs. dist. (mean bearing and sea level distance), monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with bronze cap mkd. TWO OAKS 1942.

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-23 A-C

Found - 3¼" brass cap stamped BLM 1994
23" Fir w/th healed face and tag dated 10/21/75;
N.62°E., 62.7'
32" Oak with healed face N.30°W., 47.5'