

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6482)

Set ¼ sec. post, from which
A B.Oak 10" dia., bears N.38°W., 43 lks. dist.
A B.Oak 12" dia., bears S.44°E., 86 lks. dist.

GL0 survey by Fred Mensch under Contract #757 dated Sept. 14, 1904 (DCSO records Vol. 15 Page(s) 6515)

The ¼ sec. corner, being nearly obliterated, I re-establish this corner in its original position, as follows:
Set a Porphyry stone, 15x10x6 ins., 10" in the ground, marked ¼ on N. face, from which
A Red Fir 14" dia., bears N.28°W., 15 lks. dist., marked ¼ S20 BT.
A B.Oak 12" dia., bears S.40°W., 10 lks. dist., marked ¼ S29 BT.
(Dec. 5, 1905)

J.W. Cole, County Surveyor - Wit: M.B. Hawkins, Tog Rice - March 1924 - Vol. 3 Pg. 183, Field Book 52 Pg. 55 (and "old" corner book, pg. 132)

I found a Fir stake standing from which a Fir bearing tree corresponding with field notes of Surveyor Fred Mensch. Could find no evidence of original bearing trees or rock. Fir tree dead, I marked new trees:
Fir 20" dia., N.36°30'W., 48.0 ft.
Fir 14" dia., S.8°15'E., 48.5 ft.
I set and Iron pipe 1¼" x 40", 30" in ground at corner.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland, John Powell, crew - March/April 1962 - C.S. File 49/139-32

Found - 1¼" I.Pipe and both BTs as recorded by Cole. Each BT, now stump. NW BT shows good bark scribing "BT".
New BTs -28" Laurel bears S.16°E., 41.0 ft. scribed ¼ S29 CS BT.
20" R.Fir bears S.79°W., 26.2 ft. scribed ¼ S29 CS BT.

Fd. OK, by Robert Dean, Jan. 1982, M 89-71

(Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Howard Johnstone, For: Roseburg Forest Products Co.
Dec. 28, 1989 - M 101-73 and M 101-72

Found - A 1 1/4" iron pipe.
28" Laurel bears S.16°E., 41.0 ft. healed.
20" Fir bears S.79°W., 26.2 ft. stump.
New BT - 9" Fir bears N.1°W., 33.8 ft. scribed 1/4 S20 BT.

Ronald Quimby - For: Roseburg Resources - 11/2008 - M157-4

Found - 1 1/2" iron pipe
14" Fir N.1°W., 33.8' healed face.
29" Madrone, S.16°E., 41.0' healed face.
New - 10 1/2" D.Fir N.66°E., 26.3' scribed "1/4 S20 BT"
18" D.Fir S.63°E., 24.6' scribed "1/4 S29 BT"