

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Frank Cain, Surveyor - For: G.T. Royer and H.A. Kaeppler -
January 1914 - Field Book 33 Page 35

Center of sec. 40.33 chs. South from $\frac{1}{4}$ post on North boundary
Sec. 20 and 38.45 chs. East of $\frac{1}{4}$ post West boundary.

Post marked CS 1/16S (?)

BTs - Maple 6" N.48°W., (?) lks.

 Fir 24" N.63 $\frac{3}{4}$ °E., 100 lks.

 Fir 18" S.45°W., 86 lks.

 Maple 8" S.15°E., 83 lks.

Survey by Howard Johnstone, L.S. #498 - For: Roseburg Forest
Products Co. - Dec. 28, 1989 - M 101-73 and M 101-72

Found - 17" Maple bears S.15°E., 54.8 ft. chopped out, found
 scribe.

 24" Fir bears N.63 $\frac{1}{4}$ °E., 66.0 ft., rotted stump.

 18" Fir bears S.45°W., 56.8 ft., rotted stump.

Set 5/8" x 48" Iron rod and alum. cap.

New BTs -13" Fir bears N.69°E., 11.5 ft. scribed C $\frac{1}{4}$ BT

 21" Fir bears S.12°E., 15.5 ft. scribed C $\frac{1}{4}$ BT

 18" Fir bears S.88°W., 25.5 ft. scribed C $\frac{1}{4}$ BT