

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

|   |
|---|
| <p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6484)</p> <p>-----</p> <p>Set ¼ sec. post, at average dist., from which<br/>A B.Oak 18" dia., bears N.44°W., 62 lks. dist.<br/>A B.Oak 10" dia., bears S.9°W., 180 lks. dist.</p>   |
| <p>Frank Cain - Jan. 10, 1913 - Field Book 33 Page 32 (and "old" corner book, pg. 194)</p> <p>-----</p> <p>White Oak post 4" x 4" x 3½ ft. marked ¼ S C.S., from which<br/>A Fir 12" dia., bears S.2°30'E., 28 lks.<br/>A Fir 24" dia., bears N.26¼°W., 45 lks.</p>   |
| <p>Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12831)</p> <p>-----</p> <p>Point for the ¼ sec. cor. at proportionate distance; there is no remaining evidence of the original corner.<br/>Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">¼ <math>\frac{S\ 17}{S\ 20}</math><br/>T 29 S R 6 W<br/>1958</p> <p>from which<br/>A Fir 20" dia., bears N.9°W., 68 lks. dist. mkd. ¼ S17 BT<br/>A Fir 16" dia., bears S.59°W., 192 lks. mkd. ¼ S20 BT.</p> |
| <p>Survey by Howard Johnstone, L.S. #498 - For: Roseburg Forest Products Co. - Dec. 28, 1989 - M 101-73 and M 101-72</p> <p>-----</p> <p>Found - A 26" Fir bears S.8°W., 19.0 ft. (Rec. S.2½°E., 18.5 ft. Pistol butt chopped out face and found scribe. (Cain's BT.)<br/>43" Fir bears N.26°W., 30.2 ft. (N.26¼°W., 29.7 ft. healed. (Cains BT.)</p> <p>Set 5/8" x 48" Iron rod and alum. cap at record distance from faces of Cain's NW and SE BTs.<br/>New BTs -16" Fir bears S.37°E., 32.0 ft. scribed ¼ S20 BT.<br/>12" Fir bears N.89°E., 48.2 ft. scribed ¼ S17 BT.<br/>1958 Cadastral brass cap/I.P. bears S.53°53'25"W., 102.62 ft.</p>      |
| <p>BLM resurvey by Wayne L. Rogers and Bryan S. Seibold, Cadastral Surveyors, under Group #1517, surveyed April/Aug. 1990 - (DCSO records Vol. 50 Page(s) 19171-72)</p> <p>-----</p> <p>(Cont. Next Page)</p>   |

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

| Alias | Description |
|-------|-------------|
| _____ | _____       |
| _____ | _____       |
| _____ | _____       |
| _____ | _____       |

The 1/4 sec. cor. perpetuated and recorded by Frank Cain, in 1914, from original evidence no longer in existence, further perpetuated and recorded by Johnstone, in 1989, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 16 ins. above ground, with aluminum cap, 2 ins. diam., mkd.

T 29 S RRCO R 6 W  
1/4 S  
S 17  
S 20  
1989  
LS 498

from which bearing trees mkd. by Cain

A fir, 31 ins. diam., bears S. 5½° W., 29 lks. dist., with fragmentary scribe marks in reverse and relief visible on opened blaze.

A fir, 42 ins. diam., bears N. 29¼° W., 43 lks. dist., with healed double blaze.

and bearing trees mkd. by Johnstone

A fir, 13 ins. diam., bears N. 89° E., 71 lks. dist., with scribe marks 1/4 BT visible on open blaze.

A fir, 16 ins. diam., bears S. 37¼° E., 48 lks. dist., with scribe marks 1/4 S20 BT visible on open blaze.

From this point, the ¼ sec. cor. of secs. 17 and 20 erroneously reestablished by Thielsen and White in 1958-59, bears S. 53° 47' 00" W., 1.555 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. 1/4 S17 S20 T29S R6W 1958, from which the remains of the bearing trees mkd. by Thielsen and White:

A fir snag, 19 ins. diam., bears S. 59° W., 192 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. 9° W., 68 lks. dist., with healed blaze.

The iron post was removed and the marks on the bearing trees were obliterated.