

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 240640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Arthur Boyer - For: Chas. Voitilla - Aug. 1941 - Old Vol. 4
Page 83 & C.S. 35/27

Runs from the N $\frac{1}{4}$ to the S $\frac{1}{4}$. Drawing in CS file notes Center
of sec.

Herbert Northcraft - For: Doug Rice - April/May 1972 - M44-80

Fence cor. as set by survey for Chas. Voytilla - by A. Boyer
- agreed to by Rice & Voytilla.

BLM Resurvey, by Dale B. Bedell, Surveyed under Group No 1714
Surveyed July - Oct. 1994 (D.C.S.O. records Vol. 52 Pg 19673)

Point for the center $\frac{1}{4}$ sec. cor. of sec. 5, at intersection
with the E. and W. centerline.
Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 22" in the
ground, with brass cap mkd.

T29S R6W
C $\frac{1}{4}$ S 5
1994

from which

A black oak, 33" dia., bears N.72 $\frac{1}{4}$ °E., 69 lks., mkd. C $\frac{1}{4}$
S5 BT.

A fir, 18" dia., bears N.17 $\frac{1}{4}$ °W., 79 lks. mkd. C $\frac{1}{4}$ S5 BT.
Deposit white "DEEP-1" magnetic marker at the base of the
stainless steel post.

The corner is located on a spur, slopes SE., S.35°E., 0.14
chs. from an oak fence post, 10" dia., with woven wire
fences extending S.5°E. and W.

James Klein & Michael Erickson - For: Pacific Connector Gas
Pipeline Project/Williams - Sept. 2014 - M166-23 A-C

Found - 3 $\frac{1}{4}$ " brass cap stamped BLM 1994
38" B.Oak with healed face and tag dated 10/94;
N.72 $\frac{1}{4}$ °E., 45.5'
24" Fir with healed face and tag dated 10/94;
N.71°W., 52.1' - **N.17 $\frac{1}{4}$ °W. per record & revised
map M166-37 A-C dated 6/2015 filed 8/11/2015**