

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 5: 32 T28-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5701)

Set ¼ sec. post, from which
A Y.Oak 5" dia., bears N.38°W., 54 lks. dist.
A Maple 6" dia., bears S.48°E., 40 lks. dist.

Floyd Cole, Deputy - Frank Roger; Tog Rice - June 17, 1915 - "Old" corner book, Page 108; Vol. 2 Pg. 220; F.B. 37 Pg. 55

Renew corner with Oak post 4 x 4 x 42" from original BTs and marked:
A Fir 24" dia., bears N.22°W., 8 ft.
Maple 7" dia., bears S.2½°E., 51 lks.

Arthur Boyer, Dep. Co. Surveyor - Wit. Chas. Vortilla & Douglas Rice - August 18, 1941 - C.S. File 35/27 and "Old" Cor. Bk. Page 199.

Drove 4" x 4" Fir post at corner, measuring from 6" Maple which is in. Oak to NW is gone. Found a 24" Fir which was blazed, but no record of it found. Scribed on bark of this 24" Fir which is N.5°W., 5 ft., mkd it " ¼ S32 T29S R6W CS BT

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - Dec. 1961 - C.S. File 49/139-15

Found - Both BTs as recorded by Cole in 1915.
NW BT now 30" Fir stump, cut high, shows good bark scribing "¼ S32".
SE Maple BT now down.
Set Brass cap at cor mkd: County Surveyors S32 T28S
Office, 1962 S 5 T29S R6W
New BTs- 14" Maple bears S.52°E., 23.0 ft. scribed ¼ S5 CSBT
13" R.Fir bears N.1½°E. 62.5 ft. scribed ¼ S32 CSBT
Corner is 6 ft. North of W. fence.

FD. OK, BLM Resurvey, by Dale B. Bedell, Surveyed under Group No. 1703. Surveyed Aug. 1993 thru May 1994. (D.C.S.O. records Vol. 52 Page(s)19678-79)

Fd BC & 3 BTs (NW BT stump) 1/2013 - by C. Sweeden - M164-58