

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch under Contract #757 dated Sept. 14, 1904 (DCSO records, Vol. 15 Page 6500)

Set an ironstone, 14 x 10 x 6 ins., 9½ ins. in the ground for ¼ sec. cor. marked ¼ on W. face, from which

A R.Fir 7" dia., bears S.60°E., 56 lks. dist., marked ¼ S33 BT.

A Red Fir 6" dia., bears N.63°W., 33 lks. dist., marked ¼ S32 BT.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12823)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked ¼

S 32 | S 33
T 29 S | R 6 W
1958

from which

A Fir 47" dia., bears S.32°E., 38 lks. mkd. ¼ S33 BT

A Fir 30" dia., bears N.37°W., 52 lks. mkd. ¼ S32 BT.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy - A.V. Cangie; M. Tompkins, crew - Wit: R. Mosher, BLM - Nov. 10, 1976 - C.S. File 59/26-11

Found - 30" Fir stump with illegible bark scribing bearing N.37°W., 34.3 ft.

47" Fir stump uprooted and tree removed. Stump shows visible "BT" and other illegible scribing on unhealed blaze. Also find old "BT" tag nailed on stump. Stump bears S.32°E., 25.1 ft.

A 28" x ½" I.P. with brass cap stamped properly. It was laying on top of ground over corner point. (disturbed by logging)

At corner point, We replace found 1958 brass cap and stamp "CS 1976" on brass cap.

New BTs -12" D.Fir bears S.25°E., 147.8 ft. mkd. ¼ S33 CS BT in a double blaze.

An 8" D.Fir bears S.87°W., 104.2 ft. mkd. ¼ S32 CS BT in a double blaze.

Fd. BC & 2 BTs by D. Edwards, 3/2011 - M162-22