

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by H.G. Hurlburt, Deputy Surveyor, under Contract #285, dated June 20, 1878 (DCSO records Vol 15 Pages 6493-94)

-
- Sec. Cor. 28, 29, 32 and 33.
- A Laurel 8" dia., bears N.30°W., 28 lks. dist.
 - A Live Oak 6" dia., bears S.89°W., 18 lks. dist.
 - A Fir 14" dia., bears N.50°E., 21 lks. dist.
 - A Laurel 16" dia., bears S.50°E., 22 lks. dist.

GL0 survey by Fred Mensch under Contract #757 dated Sept. 14, 1904 (DCSO records Vol. 15 Page(s) 6496)

This corner is nearly obliterated. The old cor. which was a post, has disappeared; the fir and the laurel described as bearing trees in secs.28 and 33 are still standing with marks yet distinguishable; the other bearing trees have fallen and decayed. I destroy old marks and reestablish the corner in its original position, as follows:

Set a limestone, 15 x 12 x 6 ins., 10" in the ground for cor. of secs.28, 29, 32 and 33, marked with 1 notch on S. and 4 notches on E. edge, from which:

- A Laurel 20" dia., bears N.25°E., 44 lks. dist., mkd. T29S R6W S28 BT.
- A Laurel 20" dia., bears S.26°E., 44 lks. dist., mkd. T29S R6W S33 BT.
- A Red Fir 20" dia., bears S.66°W., 65 lks. dist., mkd. T29S R6W S32 BT.
- A Chinquapin 10" dia., bears N.44°W., 53 lks. dist., mkd. T29S R6W S29 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Aug/Oct. 1956 - C.S. File 42/190-6

Point for corner determined by O.B.T.s:

- 21" Laurel bears N.25°E., 29.0 ft. I remarked S28 BT.
- 30" Laurel bears S.26°E., 29.0 ft. I rescribed S33 BT
- 20" Fir stump, logged, bears S.66°W., 43.0 ft.
- 14" Chip. bears N.44°W., 37.5 ft. Found old scribe in good condition.

At corner point, found pile of stones and Set ½" x 24" Iron rod, from which

- A 6" Chip. bears S.86°W., 14.0 ft. mkd. S32 BT.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12822-23)

(Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The sec. cor. monumented with a limestone, 15x12x10 ins., loosely set in a small mound of stone, mkd. with 1 notch on S. and 4 notches on E. edges. This cor. was established by Hurlburt in 1878. In 1904, Mensch remonumented the cor. with the described limestone and marked new bearing trees. The remaining Mensch BTs are as follows:

A Madrona 24" dia., bears N.25°E., 44 lks. dist., mkd. T29S R6W S28 BT. This tree is partly dead.

A Madrona 24" dia., partly dead and rotted, bears S.26°E., 44 lks. dist., mkd. T29S R6 on decayed blaze.

A Chinquapin 16" dia., bears N.44°W., 53 lks. dist., mkd. T29S R6W S29 BT.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked

T 29 S R 6 W
S 29 | S 28
S 32 | S 33
1958

from which new bearing trees

A Cedar 24" dia., bears N.75°E., 62 lks. dist., mkd. T29S R6W S28 BT.

A Fir 25" dia., bears S.16°E., 97 lks. dist., mkd. T29S R6W S33 BT.

A Fir 32" dia., bears N.37½°W., 47 lks. dist., mkd. T29S R6W S29 BT.

The area to the SW. of this cor. is extensively logged and no suitable bearing tree is available. Bury the limestone alongside the iron post.

DCS0-GIS Corner visitation - 8/20/2004 - Typed: 2/1/2011 - C.S. File 67/33-1

Monument - GLO/BLM 2.5" BC/IP
Comment - ok

BLM Retracement by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2300, Surveyed Aug./Sept. 2009 - (DCS0 records Vol. 56 Page(s) 22275-6 & Plat T29-6 2011)

The cor. of secs. 28, 29, 32, and 33, established by Hurlburt in 1878, perpetuated by Mensch in 1905, subsequently perpetuated by Thielsen and White in 1958, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.

from which the remains of an orig. bearing tree

A fir, 35" dia., bears N.50°E., 10.6 ft., with no marks visible. (Record 13,9 ft.)

continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of BTs mkd. by Mensch, reported by Thielsen and White

A madrone, 24" dia., bears N.25°E., 29.0 ft., with no marks visible.

A madrone, 28" dia., bears S.26°E., 29.0 ft., with no marks visible on a partially healed blaze.

A sawed fir stump, size indeterminate, bears S.62¾°W., 42.9 ft., with scribe marks T29S R6W S32 BT visible on an open blaze. (Record S.66°W., not reported by Thielsen and White)

A chinquapin, 17" dia., bears N.46¾°W., 36.6 ft., with fragmentary scribe marks visible on a partially healed blaze. (Record N. 44°W., 35.0 ft.)

and bearing trees mkd. by Thielsen and White

A cedar, 24" dia., bears N.64¾°E., 40.9 ft., with a healed blaze. (Record, N.75°E.)

A fir, 29" dia., bears N.37½°W., 31.0 ft., with scribe marks T29S R6W S29 BT visible on bark blaze.

and a new BT

A cedar, 10" dia., bears S.46¾°W., 33.6 ft., mkd. T29S R6W S32 BT.