

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6479)

- 
- Set post, cor. of secs. 16, 17, 20 and 21, from which
- A B.Oak 6" dia., bears S.65½°E., 75 lks. dist.
  - A B.Oak 6" dia., bears N.83½°E., 79 lks. dist.
  - A Pine 24" dia., bears N.57°W., 207 lks. dist.
  - A B.Oak 12" dia., bears S.25°W., 409 lks. dist.

Frank Cain - January 12, 1914 - F.B. 33 Pg. 34

- 
- Corner set by original BT, The Pine in Sec. 17 should be N.61°W., 238 lks. I renew cor. by setting a Fir post 3" x 4" x 3½ ft. marked as per instructions prefixing C.S., from which
- A Fir 18" marked C.S.S17 T29S R6W bears N.62°W., 5 lks.
  - A Fir 18" marked C.S. S21 T29S R6W bears S.62°E., 13 lks.

(This information typed from former renewal record #30 - No record source found for the following information)

- 
- Reset from one original BT in Section 21. Drove a buggy axle. Set stake marker and marked
- A 24" B.Oak N.77°E., 525.5 ft.
  - A 20" B.Oak S.75°E., 444.6 ft.
  - A 24" B.Oak N.56°W., 792.3 ft.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12825)

-----

Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked

T 29 S R 6 W  
S 17 S 16  
S 20 S 21  
1958

- from which
- A Fir 9" dia., bears N.52¼°E., 43 lks. dist., mkd. T29S R6W S16 BT.
  - A Hemlock 10" dia., bears S.73°E., 19 lks. dist., mkd. 29S R6W S21 BT.
  - A Fir 7" dia., bears S.37½°W., 47 lks. dist., mkd. T29S R6W S20 BT.
  - A Fir 12" dia., bears N.66½°W., 61 lks. dist., mkd. T29S R6W S17 BT.

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Survey by Howard Johnstone - For: Roseburg Forest Products Co. - Dec. 28, 1989 - M 101-73 and M 101-72

-----  
Found - 36" Pine bears N.61°W., 157.1 ft., down.  
22" Fir bears N.62°W., 3.3 ft. down scribe visible.  
18" Fir bears S.62°E., 8.6 ft. stump scribe visible  
Set 5/8" x 48" Iron rod and alum. cap from Cain's record 3 BTs.  
New BTs -12" Fir bears N.56°W., 57.7 ft. scribed "S17 BT"  
13" Fir bears N.36°E., 45.8 ft. scribed "16 BT"  
16" Fir bears East, 51.9 ft. scribed "S16 BT"  
9" Fir bears S.58°W., 36.2 ft. scribed "S20 BT"  
1958 Cadastral brass cap/iron pipe bears N.29°57'32"W., 50.44 ft.

Johnstone Cor. Fd. & used, BLM resurvey by Wayne L. Rogers & Bryan S. Seibold, Cadastral Surveyors, under Group #1517, surveyed April/Aug. 1990 (DCSO records Vol. 50 page 19160-61)

(Thielsen and White's erroneous cor. bears N.30°03'30"W., 0.765 chs. dist.) The 1958 Brass cap was remarked AM 1990, the iron post reset 32" in the ground, and the marks on the bearing trees were obliterated.)