



TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees mkd. by Johnstone  
A fir, 23 ins. diam., bears N. 43° E., 54 lks. dist., with  
scribe marks 1/4 S16 BT visible on open blaze.  
A fir, 14 ins. diam., bears S. 46° E., 29 lks. dist., with  
scribe marks 1/4 S16 BT visible on open blaze.  
A fir, 11 ins. diam., bears S. 2° W., 82 lks. dist., with  
scribe marks 1/4 S17 BT visible on open blaze.  
A fir, 11 ins. diam., bears N. 45° W., 48 lks. dist., with  
scribe marks 1/4 S17 BT visible on open blaze.

From this point, the 1/4 sec. cor. of secs. 16 and 17  
erroneously reestablished by Thielsen and White in 1958-59,  
bears N. 22° 14' 00" W., 0.400 chs. dist., monumented with an  
iron post, 2½ ins. diam., firmly set, projecting 8 ins. above  
ground, with brass cap mkd. 1/4 S16 S17 T29S R6W 1958, from  
which the remains of the bearing trees mkd. by Thielsen and  
White:

A root hole, bears N. 68° E., 58 lks. dist., with down  
fir, 8 ins. diam. alongside, no marks visible.  
(Record, N. 75½° E.)

A fir, 19 ins. diam., bears S. 44° W., 80 lks. dist., with  
healed blaze. (Record, S. 57½° W.)

The brass cap was remarked AM 1990, the iron post reset 32  
ins. in the ground, and all marks on the SW. bearing tree  
were obliterated.

Fd. alum cap & 4 BTs, 1/2016 by C Sweeden M170-48 A&B.