

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

|       |       |             |       |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6481)

-----

Set a post, cor. secs. 4, 5, 8 and 9, from which  
 An Ash 8" dia., bears S.17°E., 372 lks. dist.  
 A W.Oak 6" dia., bears N.88½°E., 106 lks. dist.  
 A B.Oak 14" dia., bears N.48°W., 106 lks. dist.  
 A B.Oak 10" dia., bears S.37½°W., 330 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - John Fee, Ray Irving, crew - Dec. 23, 1954 (filed Dec. 10, 1957) C.S. File 49/40

-----

Found - 3/4" Iron bolt. (see page 10-A of notes in file)  
 (Also see survey map, M 13-71)

Set 1" I.P. with brass cap mkd. County Surveyors Office

|      |       |     |
|------|-------|-----|
| T 29 | S R 6 | W   |
| S 5  |       | S 4 |
| S 8  |       | S 9 |
| 1954 |       |     |

blazed and scribed:

|           |           |           |    |      |     |    |     |
|-----------|-----------|-----------|----|------|-----|----|-----|
| 15" W.Oak | S.19½°W., | 116.0 ft. | S8 | T29S | R6W | CS | BT. |
| 10" W.Oak | N.21½°E., | 31.5 ft.  | S4 | T29S | R6W | CS | BT. |
| 15" W.Oak | N.85°W.,  | 27.6 ft.  | S5 | T29S | R6W | CS | BT. |
| 18" B.Oak | S.68°E.,  | 94.0 ft.  | S9 | T29S | R6W | CS | BT. |

Corner Fd. and used in BLM resurvey by Robert Chappel, under Group #1616, surveyed June/Sept. 1991 (DCSO records. Vol. 50 Pages 18893-94)  
 Corner is located 3 lks. W. of a fence corner, woven wire fence bears N.85°E., S.60°W., and N.10°W.

BLM Resurvey, by Dale B. Bedell, Surveyed under Group No. 1703. Surveyed Aug. 1993 thru May 1994. (D.C.S.O. records Vol. 52 Page(s)19676)

-----

The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

|       |     |     |
|-------|-----|-----|
| T29S  | R6W |     |
| S 5   |     | S 4 |
| ----- |     |     |
| S 8   |     | S 9 |
| 1954  |     |     |

(Cont. Next page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

from which bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1954 (as recorded in Douglas County Surveyor's Office corner renewal record, T.29 S., R.6 W., No. 141)

A white oak, 16 ins. diam., bears N.22°E., 48½ lks. dist., with a healed blaze.

A white oak, 26 ins. diam., bears S.19°W., 175 lks. dist., with a healed blaze.

A white oak, 27 ins. diam., bears N.85½°W., 42½ lks. dist., with a healed blaze.

and a new bearing tree

A white oak, 19 ins. diam., bears S.34 3/4°E., 141 lks. dist., mkd. T29S R6W S9 BT.

The corner is located on a SE. slope, 0.03 chs. W. of the corner of wire fences extending N., E., and SW.

Fd. ok by Ron Quimby, 4/1998 - 1998-0063 A&B

DCSO-GIS Corner visitation - 8/20/2004 - Typed: 2/1/2011 - C.S. File 67/33-1

-----  
Monument - 1¼" BC/IP  
Comment - ok