

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Cor. Secs 4 & 5; 32 & 33 T28-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5701)

Set post cor. to secs. 4, 5, 32 and 33, from which
A Y.Oak 10" dia., bears N.78½°E., 168 lks. dist.
A Y.Oak 14" dia., bears N.37½°W., 48 lks. dist.
A Y.Oak 28" dia., bears S.34°E., 260 lks. dist.
A Y.Oak 16" dia., bears S.49°W., 185 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; J. Powell - Dec. 1961 - C.S. File 49/139-17

Found - Orig. 16" now 26" Oak snag S.49°W., 117.0 ft. not 122.1 ft., shows good reverse scribing.
Orig. 10" now 24" B.Oak N.78½°E., 110.9 ft., shows good scar.
Orig. 28" now 34" Oak snag S.34°E., 166.6 ft., not 171.6 ft. shows good reverse scribing.
Orig. 14" now 32" B.Oak snag N.37½°W., 31.7 ft.

Set BC at cor. mkd: County Surveyors S32|S33 T28S R6W
Office, 1961 S 5|S 4 T29S

Fence corner thus: x x x
 ↑ x
 | / \ o sec. cor. N.35°W.

New BTs- 19" R.Fir bears West 43.0 ft. scribed S5 T29S R6W CS BT.
12" R.Fir bears N.63°W., 39.0 ft. scribed S32 T28S R6W CS BT.
9" R.Fir bears N.69°E., 8.3 ft. scribed S33 T28S R6W CS BT.
7" R.Fir bears S.87°E., 49.8 ft. scribed S4 CS BT.

Fd. BC bent, 4 BTs (W, NW, & SE stumps) by C. Sweeden, 1/2013 - M164-58

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-23 A-C

Found - 2½" brass cap stamped COUNTY SURVEYORS OFFICE 1961
29" Fir with healed face and tag dated 9/17/04; N.69°E., 8.2'

Fd. as per rec. by M Heimburger, 10/2016 - M172-47