

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 28 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by H.G. Hurlburt, Deputy Surveyor, under Contract #285, dated June 20, 1878 (DCSO records Vol. 15 Page(s) 6493)

Set 1/4 sec. post, from which
A Laurel 8" dia., bears S.40°W., 18 lks. dist.
A Laurel 7" dia., bears N.70°W., 33 lks. dist.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12822)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked
1/4 $\frac{S\ 28}{S\ 33}$
T 29 S R 6 W
1958

from which
A Pine 30" dia., bears N.37°E., 29 lks. dist., mkd. 1/4 S28 BT.
A Madrona 8" dia., bears South, 10 lks. dist., mkd. 1/4 S33 BT.