

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 340340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Victor McLind - For: Willis Creek Properties, Inc.
April 1971 - M 42-22

Set 5/8" Iron rod at center of sec. 21. Blazed and scribed
BTs as follows:

- A 15" D.Fir scribed "C $\frac{1}{4}$ S21 BT" bears S.4°E., 37.2 ft.
- A 16" D.Fir scribed "C $\frac{1}{4}$ S21 BT" bears S.67°E., 36.9 ft.

BLM Resurvey by Wayne L. Rogers and Bryan S. Seibold,
Cadastral Surveyors, under Group #1517, surveyed April/Aug.
1990 - (DCSO records Vol. 50 Page(s) 19186)

The center 1/4 sec. cor. of sec. 21, established and recorded
by McLind, Registered Land Surveyor No. 934, in 1971, and is
accepted as the corner; monumented with an iron rod, 5/8 in.
diam., firmly set, projecting 3 ins. above ground, from which
bearing trees mkd. by McLind:

- A fir, 23 ins. diam., bears S. 66 $\frac{1}{2}$ ° E., 56 lks. dist.,
with fragmentary scribe marks visible on partially
healed double blaze.
- A fir, 20 ins. diam., bears S. 2 3/4° E., 56 lks. dist.,
with healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24
ins. in the ground, directly atop the iron rod, with brass
cap mkd.

T 29 S R 6 W
C 1/4 S 21
1990

From this point, a point established as a lot corner by
McLind, 1971, bears N. 1° 01' 34" E., 0.084 chs. dist.,
monumented with an iron rod, 5/8 in. diam., firmly set,
projecting 1 in. above ground.

From this same point, a corner of which there is no record,
bears S. 29° 42' 55" E., 0.033 chs. dist., monumented with an
iron axle rod, 1 $\frac{1}{4}$ ins. diam., firmly set, projecting 1 in.
above ground.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2940, surveyed June/Sept. 2019-
(DCSO records Vol. 59 Page(s) 24017-8)

The center $\frac{1}{4}$ sec. cor. of sec. 21, reported by Rogers and
Seibold in 1990, monumented with a stainless steel post, 2 $\frac{1}{2}$ "
dia., firmly set, projecting 5" above ground, with a brass
cap (properly) mkd.

from which the remains of the bearing trees reported by
Rogers and Seibold
continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 340340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir stump, 23" dia., bears S.66½°E., 37.0 ft., with a healed blaze.
A fir snag, 22" dia., bears S.2¾°E., 37.0 ft., with a healed double blaze.
and new bearing trees
A fir, 5" dia., bears S.5¼°W., 18.6 ft., mkd. X BT.
A fir, 13" dia., bears N.59¼°W., 30.3 ft., mkd. C¼ S21 BT.
Corner is on top of ridge, bears N.70°E. and S.70°W.
From this cor., a point established as a property cor. by McLind, in 1971, reported by Rogers and Seibold, bears N.1°18'32"E., 5.48 ft. (Record, N.1°01'34"E., 5.54 ft.); monumented with an iron rod, 5/8" dia., firmly set, with top flush with the surface of the ground.
From this same cor., a point established by person(s) unknown, reported by Rogers and Seibold, for unknown purpose, bears S.27°10'33"E., 2.18 ft. (Record, S.29°42'55"E.); monumented with an iron axel rod, 1¼" dia., firmly set, projecting 1" above ground.