

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6480)

Set ¼ sec. post, at average dist., from which
A B.Oak 10" dia., bears S.21°W., 279 lks. dist.
A B.Oak 8" dia., bears N.7½°W., 222 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland, John Powell, crew - April 1962 - C.S. 49/139-41

Found - Orig. 10" now 31" W.Oak, not B.Oak, S.21°W., 184.0 ft. We open and find good scribing "S".
We also find stump hole that checks OK for NW BT.
Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 6 W
¼ $\frac{S 9}{S 16}$
1962

New BTs -Rescribed Oak BT, now 31" W.Oak S.21°W., 184.1 ft.
"¼ S16 CS BT".
11" W.Oak bears N.43°W., 57.0 ft. scribed ¼ S9 CSBT

Fd. and Use in BLM survey by Peterson and Berry, under Group #750, surveyed July/Aug. 1971 (DCSO records, Vol. 36 Pg. 14619)

Fd. OK, by Howard Johnstone, Dec. 1989, M 101-72

Fd. and Used in BLM survey by Robert Chappell, under Group #1616, surveyed June/Sept. 1991 (DCSO records, Vol. 50 Page 18890)

Fd. OK by Lang, Sept. 1996 - M 128-69.
Fd. BC & 2 BTs by C Sweeden, 1/2016 - M170-48 A&B