

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6481)

-----  
Set ¼ sec. post at average dist., from which  
A W.Oak 30" dia., bears N.60°E., 64 lks. dist.  
A W.Oak 10" dia., bears S.11°W., 100 lks. dist.

Frank Cain - For: Rice Brothers - May 27, 1915 - F.B. 37 Page 40 (and "old" corner book, Pg. 194)

-----  
Set pointed rock 7" x 8" x 14". Both original trees in place.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Ray Irving and John Fee, crew - June 1954 - C.S. File 46/45-1M

-----  
Found - 7"x8"x14" pointed rock as set by Minch in 1945 (?). 30" orig. BT, N.60°E., 42.2 ft., is down and has been down several years. Blazed face would be underneath.  
10" W.Oak, orig. BT is standing, center is rotted but believe I found a scribe mark.  
Both trees check bearings, distance and sizes w/rec.  
Blazed and scribed:  
12" R.Fir N.53°W., 37.7 ft. ¼ S4 CS BT.  
7" W.Oak S.22°W., 22.5 ft. ¼ S4 CS BT.  
Set ¾" x 30" iron rod at corner at side of rock.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy - Larry E. Monrean, Stephen Flause, crew - Aug. 16, 1977 - C.S. File 59/38-15

-----  
Found - A pointed stone, 7"x12"x16" (Rec. per Byron, 7"x8"x14"), firmly set, and a ¾" iron rod, firmly set, alongside the stone.  
The apparent remains of the orig. SW BT, an orig. 10" now 18" W.Oak, alive with previously opened blaze, center of tree is rotten, bears S.11°W., 66.0 ft.  
The location of the orig. NE BT, falls in a fire trail.  
A 12" D.Fir now a 15" rotten snag, 6 ft. tall with a well healed double blaze bears N.53°W., 36.6 ft. (Rec. N.53°W., 37.7 ft.) Byron BT.  
A 7" now 10" W.Oak, alive and well healed bears S.22°W., 22.5 ft.  
Set a 1" x 30" Iron pipe with brass cap attached marked:  
(Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas County Surveyor      1977 T 29 S R 6 W $\frac{1}{4} \frac{S 4}{S 9}$ and deposit stone and 3/4" iron rod along the West side of the brass cap. New BT - A 20" D.Fir scribed "1/4 S4 CS BT" on a double blaze bears N.81°W., 25.9 ft. Tree is located in E-W fenceline. Corner is located 3.7 ft. South of corner of fences running E-W and South.
Corner Fd. and used in BLM survey by Robert Chappel, under Group #1616, surveyed June/Sept. 1991 (DCS0 records, Vol. 50 Pages 18894-95)
Fd. ok by Ron Quimby, 4/1998 - 1998-0063 A&B