

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33, 34; 3 & 4 T30-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6459)

Set a post, at proper dist., cor. of secs. 3, 4, 33 and 34, from which

- A R.Fir 4" dia., bears N.75°E., 36 lks. dist.
- A R.Fir 10" dia., bears S.72°E., 115 lks.
- A Laurel 4" dia., bears S.27°W., 40 lks.
- A Cedar 4" dia., bears N.65°W., 17 lks.

Doug. County Surveyors Office - James Byron, Deputy - For: Dale Weekly - May 15, 1956 - C.S. File 47/93

Location of corner determined by facing two old BTs not of record. (see letter attached to notes in C.S. 47/93)

Found - Old BT, 50" Fir, N.2°W., 36 ft., fd. scribe S34.
Old BT, W.Fir, snag only, S.7°E., 14 ft. found scribe T.R.W. 35.

Set an I.P. with brass cap for cor. mkd: $\frac{33|34}{4|3}$

Blazed and scribed new trees:

- 12" W.Fir N.19°W., 62.4 ft. mkd. "T29S R6W S33 CS BT".
- 26" W.Fir N.63°30'E., 87 ft. mkd. "T29S R65W S34 CS BT".
- 18" W.Fir S.55°30'E., 39 ft. mkd. "T30S R6W S3 CS BT".
- 4" R.Fir S.60°W., 18.5 ft. mkd. "S4 CS BT".

BLM resurvey by Thielsen and White, under Group #'s 348 and 350. Surveyed, July 1958/Aug. 1959 (DCSO records, Vol. 30 Pages 12809-10)

The Sec. cor. perpetuated with an I.P. 1" dia., 10" above ground, firmly set, with DCSO brass cap. Monument was set by Byron in 1956 from bearing trees not of record. I accept this monument as the best available evidence of the original corner point.

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd:

T 29 S R 6 W
S 33 | S 34
S 4 | S 3
T 30 S
1958

from which bearing trees not of record, found by Byron:

- A Fir 50" dia., bears N.4¼°W., 54 lks. dist., mkd. with an open blaze and parts of scribe marks.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33, 34; 3 & 4; of T30-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Fir snag 40" dia., bears S.9°E., 21 lks. dist., mkd. with an open blaze and parts of scribe marks. and bearing trees mkd. by Byron in 1956:
A Fir 26" dia., bears N.62°E., 130½ lks. dist., mkd. T29S R6W S34 CS BT.
A Fir 18" dia., bears S.57°E., 59 lks. dist., mkd. T29S R6W S3 CS BT.
A Fir 4" dia., bears S.58¼°W., 28 lks. dist., mkd. S4 CS BT.
A Fir 12" dia., bears N.20½°W., 93½ lks. dist., mkd. T29S R6W S33 CS BT.
I correct the marks on the SE. tree to read T30S R6W S3 CS BT and bury the County Surveyor's monument alongside the I.Post.

BLM resurvey by Roseberry, under Group #649. Surveyed Aug/Sept. 1967 (DCSO records, Vol. 35 Pages 14347-48)

The sec. cor. rehabilitated by Thielsen and White in 1958, monumented with an I.P. 2½" dia., protruding 6" above the ground, firmly set, with brass cap, from which the bearing trees described by Thielsen and White in 1968:

A shattered W.Fir 30" dia., bears N.62°E., 130½ lks. dist., with scribe marks t29S R6W S34 CS BT visible on open blaze.
A W.Fir 18" dia., bears S.57°E., 59 lks. dist., with a healed blaze.
A W.Fir snag 40" dia., bears S.9°E., 21 lks. dist., with scribe marks T30S R6W S3 BT visible on opened blaze.
A W.Fir 17" dia., bears N.20½°W., 93½ lks. dist., with scribe marks T29S R6W S33 CS BT visible on open blaze.
A stump hole bears N.4¼°W., 54 lks. dist., alongside of which is an uprooted and sawed Fir stump 50" dia., with no visible marks.
and new bearing trees:
A W.Fir 8" dia., bears N.20¼°E., 118½ lks. dist., mkd. T29S R6W S34 BT.
A Fir 12" dia., bears S.3°W., 52½ lks. dist., mkd. T30S R6W S4 BT.

Text from correspondance from Howard Johnstone, Feb. 22, 1978 C.S. File 47/93

"The corner renewal records show that Jim Byron, Deputy County Surveyor, set I.P.B.C. at (this corner) from old bearing trees, not of record, in 1956, and that the cadastral (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 and 34; 3 & 4 of T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

surveyor set their brass caps alongside the county brass cap, also referring to the old bearing trees, not of record, in 1958.

We have also found these old fir bearing trees at (section corner) opened up the faces and found excellent scribe marks. We also counted the growth rings since the trees were scribe(sic) and determined that the trees were scribe(sic) about 120 years ago which would be about 1855. This was the year that the cadastral surveyor, Nathaniel Ford, surveyed these section lines. Based on this evidence, it is my opinion that these bearing trees are the original bearing trees for the section corner, even though the records for (corner) indicate different bearings, distances, and species. I feel that the original corner record data was transposed with some other corners when it was copied into the official notes of record and that the brass cap monument currently set (is) as close to the location of the original corner post as can possibly be determined by the intersection of lines projected out from the faces of these original bearing trees."

Fd. and accepted corner, BLM resurvey, Jelley & Rogers, 1980, DCSO records, Vol. 42 Pages 16560-61)

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed April/June 2002, - (DCSO records Vol. 54 Page(s) 21130-1)

 The cor. of secs. 3, 4, 33, & 34, on the S. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground (with an iron pipe, 1" dia., projecting 16" above ground alongside, with brass cap mkd. COUNTY SURVEYORS OFFICE T29S R6W 3 4 33 34 1956 T30S R6W), with brass cap mkd.

T29S R6W
S 33|S 34
 S 4|S 3
 T 30 S
 1958

from which the remains of bearing trees mkd. by the Douglas County Surveyors Office, in 1956, reported by Thielsen, White, and Roseberry

- A decayed fir stump, size indeterminate, bears N.62°E., 86.1 ft., with no marks visible.
- A fir, 28" dia., bears S.57°E., 38.9 ft., with a healed blaze.
- A fir, 29" dia., bears N.20½°W., 61.7 ft., with a healed double blaze.

continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33, 34; 3 & 4 T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of bearing trees mkd. by Roseberry
A fir, 21" dia., bears N.20°E., 77.2 ft., with a healed blaze. (Record, N. 20¼°E., 78.2 ft.)
A fir snag, 21" dia., bears S.32°W., 34.7 ft. with a healed blaze. (Record, S.3°W.)
and a new bearing tree
A fir, 16" dia., bears S.53¼°W., 61.3 ft, mkd. T30S R6W S4 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
The geographic position (NAD 1983 (CORS)) of this cor. as determined by NAVSTAR Global Positioning System (GPS), utilizing dual frequency, carrier phase GPS receivers, (Trimble 5700), relative to the National Spatial Reference System, is as follows:
Latitude: 42°59'55.14"N., Longitude: 123°24'18.72"W.