

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 15 Page(s) 6492)

Set ¼ sec. post, from which
A Laurel 30" dia., bears N.50°E., 115 lks. dist.
A W.Oak 30" dia., bears N.32°W., 31 lks. dist.

J. W. Cole, Surveyor - For: Rice Bros., Brecht and M.B. Hawkins - Wit: A.E. Rice; M.B. Hawkins; Hyman Huntley - Feb. 27, 1924 - F.B. 52 Page 48; Vol. 3 Pg. 183

This corner renewed from orig. bearing trees, both of which were standing, both trees bearing scribe marks:
A W.Oak 30" dia., N.30°W., 20.5 ft.
A Laurel 40" dia., N.42°E., 75.2 ft.
Set an Oak post, 4"x4"x40". Also 1"x40" galv. Pipe.
Marked new trees as follows:
A Fir 12" dia., N.77°45'E., 20.0 ft.
A Fir 16" dia., N.13°W., 42.2 ft.

Douglas Co. Surveyors Office - James Byron, Party Chief - Ray Irving; John Fee, crew - June 7-14, 1954 - C.S. File 46/45-1(A&B)

Found - Orig. 30" Laurel, is down and center is rotted. No scribes visible. Old blaze for BT faces OK. bearing is N.40°E., 115 lks.
Orig. 30" W.Oak N.32°W., 31 lks. is standing but center is rotted. No scribing visible.
Set 1" pipe with brass cap from orig. BTs mkd: County Surveyors Office, 1954, ¼S 28|27 T29S R6W.
Blazed and scribed:
8" Cedar S.45°W., 22.8 ft. mkd. ¼ S28 CS BT.
20" R.Fir N.40°E., 15.4 ft. mkd. ¼ S27 CS BT. Bark scribed.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12819)

The ¼ sec. cor., monumented with an iron post, 1" dia., 10" above ground, firmly set, with 1954 county brass cap, from which the original bearing trees:
A Madrona, dead, down and rotted, bears N.42½°E., 115 lks. dist., no marks remain. (Rec. bearing N.50°E.)
A W.Oak 34" dia., bears N.32°W., 31 lks. dist., mkd. with illegible scribe marks.

(Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point
Set an iron post, 28 ins. long, 2½ ins. dia., 20 ins. in the ground, with brass cap mkd:

¼
S 28 | S 27
T 29 S | R 6 W
1958

from which a bearing tree mkd. by the county Surveyor:

A Fir 20" dia., bears N.40°E., 23½ lks. dist., mkd. ¼ S27
CS BT.

and a new bearing tree:

A W.Oak 11" dia., bears S.29°W., 37 lks. dist., mkd. ¼ S28
BT.

Bury the County Surveyor's monument alongside the iron post.

Fd. OK, by Burton Holt, Oct. 1983, M 95-35

BLM Resurvey by Wayne L. Rogers and Bryan S. Seibold, Cadastral Surveyors, under Group #1517, surveyed April/Aug. 1990 - (DCSO records Vol. 50 Page(s) 19192)

The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. in 1958.

from which the remains of a bearing tree mkd. by Cole, in 1924

A sawed fir stump, 12 ins. diam., bears N. 81 3/4° E., 32 lks. dist., with fragmentary scribe marks visible on open blaze.

and the remains of a bearing tree mkd. by Byron, in 1954

A sawed fir stump, 27 ins. diam., bears N. 40° E., 23½ lks. dist., no marks visible.

and a bearing tree mkd. by Thielsen and White

A white oak, 16 ins. diam., bears S. 29° W., 37 lks. dist., with healed blaze.

and a new bearing tree

A white oak, 13 ins. diam., bears S. 10¼° E., 55 lks. dist., mkd. 1/4 S27 BT.

Fd. Ok by K. DeGroot, 10/2009 - 2009-0053A&B