

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6476)

Set ¼ sec. post, from which
A B.Oak 6" dia., bears S.46½°W., 75 lks. dist.
A Red Fir 24" dia., bears S.48°E., 62 lks. dist.

Survey by Victor McLind - For: Willis Creek Properties - July 1971 - M 42-33

No evidence of corner found.
Set 5/8" Iron rod and blazed and scribed BTs as follows:
12" D.Fir scribed "T29S R6W ¼ S16 BT" bears S.5°W., 27.5 ft.
12" Maple scribed "T29S R6W ¼ S15 BT" bears S.87°E., 46.5 ft.

BLM resurvey by Peter Peterson and Daniel Berry under Group #750, surveyed July/Aug. 1971 (DCSO records Vol. 36 Page(s) 14615)

The ¼ sec. cor., reestablished by proportionate measurement by V. McLind, in 1971, monumented with an iron rod, ½" dia., firmly set, protruding 5" above ground, from which a bearing tree marked by McLind:

A Maple 17" dia., bears S.88°E., 76 lks. dist., with scribe marks T29S R6W 1/4 S15 BT visible on open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

1/4
S 16 | S 15
T 29 S R 6 W
1971

from which a new bearing tree

A Fir 11" dia., bears S.5°W., 42 lks. dist., marked 1/4 S16 BT.

Deposit the iron rod alongside the iron post.
Corner located on spur, slopes NE.

Fd. OK, by Kris DeGroot, Feb. 1987, M 103-47

Fd. OK by Howard Johnstone Dec. 1989 - M 101-72

FD. BC & 2 BTs by C Sweeden 1/2016 - M170-48 A&B