

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec Cor for 9, 10, 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6476)

-----  
Set post, cor. of secs. 9, 10, 15 and 16, from which  
An Ash 8" dia., bears S.25°E., 284 lks. dist.  
An Alder 6" dia., bears N.61°E., 275 lks. dist.  
A B.Oak 16" dia., bears N.23°W., 215 lks. dist.  
An Ash 12" dia., bears S.37°W., 278 lks. dist.

Survey by Victor McLind - For: Willis Creek Properties - July 1971 - M 42 - 33

-----  
No evidence of corner found. I renewed corner by double proportionate measurement from corners shown.  
Set 5/8" Iron rod in mound of stone.  
Blazed and scribed new bearing trees as follows:  
12" Alder scribed "T29S R6W S10 BT" bears N.48°E., 158.1 ft.  
40" B.Oak scribed "T29S R6W S9 BT" bears N.74°W., 157.2 ft.  
26" B.Oak scribed "T29S R6W S15 BT" bears S.42°E., 255.0 ft.

BLM resurvey by Peter Peterson and Daniel Berry under Group #750, surveyed July/Aug. 1971 (DCSO records Vol. 36 Page(s) 14615-16)

-----  
The Sec. cor., reestablished by proportionate measurement by McLind, in 1971, monumented with an iron rod 1/2 in. dia., firmly set, protruding 6" above ground, from which bearing trees marked by McLind:

An Alder 13" dia., bears N.49°E., 240 lks. dist., with scribe marks T29S 6W S10 BT visible on open double blaze.  
A W.Oak 24" dia., bears S.41°E., 385 lks. dist., with scribe marks T29S R6W S15 BT visible on open double blaze.  
A W.Oak 27" dia., bears N.73°W., 240 lks. dist. with scribe marks T29S R6W S9 BT visible on open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 29 S R 6 W  
S 9 | S 10  
S 16 | S 15  
1971

No suitable tree available within limits in sec. 16.  
Deposit the iron rod alongside the iron post

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec Cor for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Randall Smith, Deputy -  
Stephen Flause, crew - Aug. 11, 1992 - C.S. File 64/32-4  
-----

- Found - 3¼" BLM brass cap on a 2½" O.D. Iron pipe protrudes  
8" above ground. (1971)  
3/4" I.Rod protrudes 10" above ground along West  
edge of BLM BC/IP (Set by RLS #934 in 1971)  
13" now 15" dia., 3 ft. high split Alder stump with  
a partially healed double blaze, scribing visible  
"29S R6W S10" bears N.49°E., 158.4 ft. (agrees  
w/rec)  
24" now 29" dia. B.Oak with a fully healed double  
blaze, bears S.41°E., 254.1 ft. (agrees w/rec)  
27" now 40" dia., down Oak with a partially healed  
double blaze scribing visible "T29S R6W S9" bears  
N.73°W., 155.6 ft. (Rec. N.73°W., 158.4 ft.),  
possible slope measurement)

New Accessories:

- PPL Power pole with tags "PPL 40T", "PPL SW97", "PPL  
B7909" bears N.33½°E., 97.8 ft.
- 4" Maple double blazed and scribed "X BT" bears  
S.84½°E., 46.9 ft.
- 6" Cedar double blazed and scribed "X BT" bears  
S.60½°W., 111.7 ft.

Fd. OK by Lang, Sept. 1996 - M 128-69  
Found OK by M. Heimburger, Sept. 2002 - M140-78  
Fd. BC & B0s of record by N Hibbs, 9/2019 M176-48  
Fd 1971 Brass cap by Bart Heichel - 5/2025 - M186-10