

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 34; & 3 of T30-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6458)

-----

Set ¼ sec. post, at proper dist., from which  
 A W.oak 7" dia., bears N.75°E., 76 lks.  
 A W.Oak 10" dia., bears S.72°E., 115 lks.

Doug. County Surveyors Office - James Byron, Deputy - For: Dale Weekly - May 15, 1956 - C.S. File 47/93

-----

Original BTs not found. Corner set midway and on true line between section corners.  
 Set an I.P. with brass cap mkd: ¼ S34/3 T29S R6W Co. Surveyors Office, 1956.  
 Scribed two trees:  
 36" Fir N.36°E., 22.7 ft. mkd. "¼ S34 T29S R6W CS BT".  
 A Fir S.60°E., 37.0 ft. mkd. "¼ S3 T29S R6W CS BT".

BLM resurvey by Thielsen and White under Group #'s 348 & 350. Surveyed July 1958/Aug. 1959 (DCSO records, Vol. 30 Pg 12841)

-----

The ¼ sec. cor. is monumented with an I.P. 1" dia., 10" in the ground, firmly set, with DCSO brass cap. Records show that this monument was set by Byron, who reestablished the cor. at midpoint and on line bet. the section corners.

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd:

T 29 S R 6 W  
                   ¼ S 34  
                           S 3  
 T 30 S R 6 W  
 1958

from which bearing trees mkd. by Byron:

A Fir 36" dia., bears N.37°E., 34½ lks. dist., mkd. T29S R6W ¼ S34 CS BT.

A Fir 42" dia., bears S.59½°E., 57 lks. dist., mkd. T30S R6W S3 CS BT.

Bury the County Surveyor's monument alongside the iron post.

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1551, Surveyed Aug/ 1990/July 1991 - (DCSO records Vol. 50 Page(s) 19211)

-----

The ¼ sec. cor. of secs. 3 and 34 on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set,  
 (Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; and S. 3, T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

projecting 6 ins. above ground, with brass cap mkd.

T29S R6W

S34

¼

S3

T30S R6W

1958

from which the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1956

A root hole, bears N. 37° E., 34½ lks. dist., with a down fir stump alongside, 40 ins. diam., with scribe marks ¼ S34 CS BT visible on the bark.

A root hole, bears S. 59½° E., 57 lks. dist., with a down fir alongside, 45 ins. diam., with scribe marks visible on the bark.

and new bearing trees

A Douglas fir, 12 ins. diam., bears N. 46° E., 14 lks. dist., mkd. ¼ S34 BT.

A white fir, 12 ins. diam., bears S. 20° W., 18 lks. dist., mkd. ¼ S3 BT.

The corner is located 15 lks. E. of an abandoned dirt road, 20 lks. wide, bearing N. 30° E. and S. 30° W.