

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 15 Page(s) 6491)

Set ¼ sec. post, from which
A Fir 8" dia., bears S.40°W., 41 lks. dist.
A Fir 8" dia., bears N.20°W., 35 lks. dist.

Cadastral survey by Hans W. Thielsen and C. Albert White under Group #s 348 and 350. Surveyed, July 23, 1958 to Aug. 5, 1959 (DCSO records Vol. 30 Page(s) 12818)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. dia., 20 ins. in the ground, with brass cap mkd: ¼ $\frac{S\ 27}{S\ 34}$
T 29 S R 6 W
1958

from which
A Fir 23" dia., bears N.39½°E., 41 lks. mkd. ¼ S27 BT.
A Fir 19" dia., bears S.42°W., 22½ lks. mkd. ¼ S34 BT.
The ¼ sec. cor. is located on small spur, slopes N.

BLM Resurvey by Wayne L. Rogers and Bryan S. Seibold, Cadastral Surveyors, under Group #1517, surveyed April/Aug. 1990 - (DCSO records Vol. 50 Page(s) 19189-90)

The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, in a collar of stone, with brass cap mkd. in 1958. from which the remains of the bearing trees mkd. by Thielsen and White
A fir, 24 ins. diam., bears N. 39½° E., 41 lks. dist., with partially healed blaze.
A fir snag, 19 ins. diam., bears S. 42° W., 22½ lks. dist., with healed blaze.
and a new bearing tree
A fir, 11 ins. diam., bears S. 81½° W., 118½ lks. dist., mkd. 1/4 S34 BT.

From this point, the Bureau of Land Management Geodetic Control Station No. EC41047, at latitude 43° 01' 33.107" N., longitude 123° 23' 54.293" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears N. 14° 30' 33" W., 70.288 chs. dist. (mean bearing and sea level distance), monumented with an aluminum cap, firmly set flush in

concrete, with top mkd. EC41047 GPS 1990.
