

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6475)

-----  
Set ¼ sec. post, at average dist, from which:  
A B.Oak 10" dia., bears N.36°E., 81 lks. dist.  
A B.Oak 8" dia., bears S.70°E., 98 lks. dist.

Douglas Co. Surveyors Office - Arthur Boyer, D.C.S. - Wit: N. Richardson, Victor Phipps, Ruben Moore, Geo. Stephens - March 10, 1937 - Vol. 4 Pg. 39; C.S. File 30/12; (and "old" cor. book, page 194)

-----  
Reestablished from original two BTs which are badly decayed and hollow.  
Set 5/8" Iron bolt 36" long, nut on top, beside 15" W.Fir which is blazed. Marked following two trees:  
A 24" Fir, bark blaze, N.44½°W., 18.0 ft.  
An 8" Fir, S.4½°E., 25.5 ft.

BLM resurvey by Peter Peterson and Daniel Berry under Group #750, surveyed July/Aug. 1971 (DCSO records Vol. 36 Page(s) 14613)

-----  
The ¼ sec. cor., perpetuated by Boyer in 1937, from original evidence no longer in existence, monumented with an iron pipe, 1/2 in. dia., firmly set, protruding 6 ins. above ground, from which bearing trees marked by Boyer  
A Fir snag 26" dia., bears N.44°W., 27 lks. dist., with healed blaze.  
A Fir 15" dia., bears S.4°E., 38 lks. dist., with healed blaze.

At the corner point  
Set an iron post, 28 ins. long, 2½ ins. dia., 24 ins. in the ground, with brass cap mkd:  
1/4  $\frac{S \ 15}{S \ 22}$   
T 29 S R 6 W  
1971

from which a new bearing tree  
A Fir 26" dia., bears N.14°W., 86 lks. dist., marked 1/4 S15 BT.  
Deposit iron pipe alongside the iron post.  
Corner located on spur, slopes S.20°E.

David Edwards - For: Steele & Son Resources LTD - 11/2015 - M170-19

-----  
Found - 23" dia., Fir bears S.4°E., 25.1 ft.  
27" dia., Fir stump bears N.14°W., 56.8 ft (cont.)

