

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6477)

Set ¼ sec. post at average dist., from which
 A B.Oak 12" dia., bears N.15°W., 79 lks. dist.
 A B.Oak 6" dia., bears S.89°W., 77 lks. dist.

G.G. Stewart - For: Rice Brothers - Wit: Abner Rue, J.H. Adams, Dick Redding, H. Erskine - April 17, 1922 - Vol. 3 Pg. 118 (and "old" corner book, pg. 131)

Set Iron pipe according to Government field notes, distances from BTs. Found both BTs, one badly rotted. Marked:
 An 8" Laurel S.2°W., 67.7 ft.
 An 18" B.Oak N.14°W., 52.1 ft. Old BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Fee Ray Irving, crew - June 1954 - C.S. File 46/45-1(K)

We found both BTs as established by Stewart, 1922 -
 8" Laurel S.2°W., 67.7 ft. standing but dead, scribed ¼ CS BT.
 18" B.Oak N.14°W., 52.1 ft., standing, dead, blaze grown over.
 Both BTs check for bearings and distances.
Set 3/4" Iron rod at corner.
Blazed and scribed:
 8" R.Fir N.7°W., 37.8 ft. dist. ¼ S3 CS BT.
 8" R.Fir S.13°E., 18.2 ft. dist. ¼ S10 CS BT.
We could not find pipe set by Stewart in 1922.