

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 26 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 5469)

Set ¼ sec. post, from which
A B.Oak 18" dia., bears N.43°W., 72 lks. dist.
A B.Oak 12" dia., bears S.63°E., 84 lks. dist.

Survey by Howard Johnstone - For: Roseburg Lumber Co. - April 1978 - RM 3-12

At midpoint, Set 5/8" x 30" Iron rod and alum. cap.
BTs - 8" Yew N.86°E., 28.5 ft.
10" Cedar S.7°W., 21.8 ft.
Corner is 119.72 ft. South of ¼ cor. for Sec. 27, bearing N.1°02'24"E.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2940, surveyed June/Sept. 2019- (DCSO records Vol. 59 Page(s) 24008-9)

The ¼ sec. cor. of sec. 26 only, reestablished by Johnstone, in 1978; there is no remaining evidence of the original cor. and this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 10" above ground, with a yellow plastic cap mkd. LS, from which the bearing trees mkd. by Johnstone
A yew, 11" dia., bears N.85¼°E., 28.8 ft., with scribe marks ¼ visible on open blaze.
A cedar, 25" dia., bears S.13¼°E., 11.3 ft., with a healed blaze.

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 20" in the ground, directly over the iron rod, with brass cap mkd.

T29S R6W
| ¼
| S 26
2019

Corner is located W., 11 ft., of wire fence, extends N. & S.