

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6470)

-----

Set post, cor. of secs. 14, 15, 22 and 23, from which  
 A W.Oak 14" dia., bears N.24°E., 500 lks. dist.  
 A Laurel 4" dia., bears S.44½°W., 362 lks. dist.  
 A B.Oak 14" dia., bears N.38°W., 432 lks. dist.  
 For Sec. 23, no tree within a reasonable distance.

F.C. Frear, Deputy Co. Surveyor - For: O.W. Ronk, Fred Smith and L.N. Sargisson - May 1919 - Field Book 46 Pgs. 47-57; Vol. 3 Pgs. 62-64 and "old" cor. book, Pg. 129

-----

I re-establish from old BT, namely a 30" W.Oak, N.24°E., 5.00 chs. which I remark and Set a 1" x 30" Iron pipe and 3" x 36" Oak stake, from which  
 An 18" Fir bears N.16°W., 22¾ lks. C.S.B.T.  
 A 12" Fir bears N.83¾°W., 42½ lks. C.S.B.T.  
 A 24" Fir bears S.29½°E., 32 lks. C.S.B.T.  
 A 14" Fir bears N.44½°E., 40 lks. C.S.B.T.

Douglas Co. Surveyors Office - James Byron, Deputy - June, 1954 - C.S. File 46/45-1(E)

-----

Found - 1" I.P. at corner. Also an 18" R.Fir stump, scribed S14 BT., N.42°E., 26.5 ft. May have been scribed 25 yrs. ago  
 18" R.Fir S.80°W., 30 ft. has old blaze, we did not cut out.  
 30" R.Fir S.28°E., 20.6 ft., has old blaze, we did not cut out.  
 All trees are healthy and in good condition.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland and John Powell, crew. - April/May 1962 - C.S. File 49/139-46

-----

Found - NW., SE., and NW. BTs as recorded by Frear, all now stumps. We open N.83¾°W., 28.0ft. BT and find good scribing.  
 Do not find I.P. set at cor. There has been cat work in area.  
 Set Brass cap at cor. mkd: County Surveyors Office

T 29	S R 6 W
S 15	S 14
S 22	S 23
1962	

(Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -5" R.Fir bears S.68°W., 51.6 ft. scribed S22 CS BT.  
8" W.Oak bears N.47°E., 93.4 ft. scribed S14 T29S  
R6W CS BT.  
20" R.Fir bears N.26°W., 78.3 ft. scribed S15 T29S  
R6W CS BT.

Fd. Ok DCSO, LEM - PLE - JHC, 12/3/1975 - C.S. 57/39-25

BLM resurvey by Peter Peterson and Daniel Berry under Group #750, surveyed July/Aug. 1971 (DCSO records Vol. 36 Page(s) 14610-11)

-----  
The Sec. cor., perpetuated by Frear in 1919, further perpetuated by Byron in 1962, monumented with an iron post, 1½" dia., firmly set, protruding 6" above ground with 1962 DCSO brass cap.

from which the only remaining original bearing tree  
A W.Oak 39" dia., bears N.24°E., 500 lks. dist., with healed blaze.

and bearing trees marked by Frear in 1919  
A Fir stump 32" dia., bears S.29°E., 33 lks. dist., with fragmentary scribe marks visible on open blaze.

A Fir stump 18" dia., bears N.83°W., 43 lks. dist., with no marks visible on opened blaze.

and bearing trees marked by Byron in 1962  
A W.Oak 10" dia., bears N.47°E., 141 lks. with healed blaze.

A Fir 9" dia., bears S.67°W., 82 lks., with healed blaze.  
A Fir snag 23" dia., bears N.27°W., 119 lks., with scribe marks T29S R6W S15 CS BT visible on opened blaze.

and new bearing trees  
A Fir 14" dia., bears S.25°E., 248 lks mkd T29S R6W S23 BT  
A Cedar 7" dia., bears N.35°W., 77 lks mkd T29S R6W S15 BT

Fd. OK, by Donald Bentz, April 1983, C.S. File 58/282