

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6471)

-----  
Set post, cor. of secs. 10, 11, 14 and 15, from which  
A B.Oak 10" dia., bears N.37°E., 460 lks. dist.  
A B.Oak 12" dia., bears N.7°W., 435 lks. dist.  
A Laurel 4" dia., bears S.58°W., 240 lks. dist.  
A Laurel 4" dia., bears S.12°E., 110 lks. dist.

F.C. Frear, Deputy Co. Surveyor - For: O.W. Ronk, Fred Smith, L.N. Sargisson - May 1919 - F.B. 46 Pgs. 47-57; Vol. 3 Pgs. 62-64 - (and "old" corner book, pg. 130)

-----  
Renewed from old BTs by setting a 5" x 5" x 40" Oak stake from which  
A 10" Laurel bears N.44°E., 13½ lks. C.S.B.T.  
A 20" Fir bears S.62¼°E., 18 lks. C.S.B.T.  
A 20" Fir bears S.75°W., 39 lks. C.S.B.T.  
A 12" Fir bears N.63¼°W., 30 lks. C.S.B.T.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland, John Powell, crew - April 1962 - C.S. 49/139-43

-----  
Found - 1" I.P. at cor. and all BTs as recorded by Frear. SE and SW BTs, now stumps, show good scars. NE BT, now down and partly rotted. We open NW BT and find good scribing.  
Corner bears S.9°W., 18 ft. from a fence corner, fences running N-S and W.  
New BTs -13" R.Fir bears S.25°E., 40.1 ft. scribed S14 T29S R6W CS BT.  
10" Laurel bears S.56°W., 34.4 ft. scribed S15 T29S R6W CS BT.  
10" R.Fir bears N.9°E., 14.5 ft. scribed S11 CS BT.

BLM resurvey by Peter Peterson and Daniel Berry under Group #750, surveyed July/Aug. 1971 (DCSO records Vol. 36 Page(s) 14612)

-----  
The Sec. Cor., perpetuated by Frear in 1919, when original corner evidence was existent, further perpetuated by Byron in 1962, monumented with an iron pipe, 1" dia., firmly set, protruding 4" above ground, from which bearing trees marked by Byron in 1962  
A Fir 13" dia., bears N.8°E., 22 lks. with healed blaze.  
A Fir 17" dia., bears S.23°E., 61 lks. with healed blaze.  
A Madrone 13" dia., bears S.57°W., 53 lks. with scribe marks T29S R6W S15 CS BT visible on open blaze.

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

At the corner point  
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in  
the ground, with brass cap marked

T 29 S R 6 W  
S 10 | S 11  
S 15 | S 14  
1971

from which a new bearing tree  
A Fir 13" dia., bears N.63°W., 130 lks. dist., marked T29S  
R6W S10 BT.  
Deposit iron pipe alongside the iron post.

Fd. OK, by Herman Pieske, Oct. 1986, M 102-55