

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6472)

-----  
Set post, cor. secs. 2, 3, 10 and 11, from which  
A W.Oak 10" dia., bears S.7°E., 17 lks. dist.  
A B.Oak 8" dia., bears N.82½°W., 109 lks. dist.  
A W.Oak 4" dia., bears N.73½°E., 71 lks. dist.  
A B.Oak 16" dia., bears S.21½°W., 31 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - M. Godfrey; S. Bilow, crew - Dec. 27, 1957 - C.S. File 49/52-1

-----  
Found three of the original BTs. All check for bearing & distance.

The orig. NW BT now 30" B.Oak is alive. Shows old scar. I do not open.

The orig. SW BT now 36" snag, shows old scar. I do not open.

The orig. 4" W.oak now 22" N.73½°E., 46.9 ft. I open and find good scribe "BT"

Set Brass cap at cor. mkd: County Surveyors

S 3 | S 2  
S 10 | S 11  
Office  
1957

(See sketch in file for relation of brass cap to fence cor.)  
New BTs -8" W.Oak bears N.83°W., 34.0 ft. scribed T29S R6W S3 CS BT.

10" W.Oak bears S.35½°W., 75.3 ft. scribed T29S R6W S10 CS BT.

6" B.Oak bears S.71°E., 63.8 ft. scribed T29S R6W S11 CS BT.

12" Laurel bears N.79°E., 9.0 ft. scribed T29S R6W S2 CS BT.