

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 35; & 2 T30-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6458)

-----  
Set ¼ sec. post at proper dist., from which  
A W.Oak 6" dia., bears S.70°E., 60 lks.  
A W.Oak 8" dia., bears N.75°E., 200 lks.

-----  
Doug. County Surveyors Office - James Byron, Deputy - For:  
Dale Weekly - May 15, 1956 - C.S. File 47/93

-----  
Corner set half way between section corners.  
Set an I.P. with brass cap mkd: S 35 T29S R6W  
County Surveyors Office, 1956 ¼ Cor. S 2 T30S  
From which:  
A 14" W.Oak bears N.5°30'E., 29.0 ft. scribed "¼ S35 T29S  
R6W CS BT".  
A 12" W.Oak bears S.51°E., 233.37 ft. scribed "¼ S2 T30S  
R6W CS BT".

-----  
Kris DeGroot - For: C & D Lumber Co. - 6/2003 - M 142-44

-----  
Found - 1" iron pipe by Byron in 1956, firmly set,  
projecting 12" above the ground with 2½" brass  
cap (properly) stamped, from which Byron's BTs:  
20" W.Oak bears N.5°30'E., 28.7 ft. with healed  
blaze (rec. N.5°30'E., 29.0 ft.)  
19" W.Oak bears S.51°00'E., 233.4 ft. with a healed  
blaze (rec. S.51°E., 233.37 ft.)  
New RMS- 5/8"x30" iron rod set 28" in the ground with plastic  
cap "BTS ENG-SURV" bears S.5°29'43"W., 25.00 ft.  
5/8"x30" iron rod set 28" in the ground with plastic  
cap "BTS ENG-SURV" bears N.51°00'54"W., 25.00 ft.