

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6469)

Set ¼ sec. post at average distance, from which
 A W.Oak 15" dia., bears N.33°W., 87 lks. dist.
 A B.Oak 18" dia., bears S.43°E., 122 lks. dist.

Survey by Frank Cain - For: J.F. Pefley - Wit: Hyman Huntley & J.M. Ledgerwood - Nov. 10, 1913 - Field Book 33 Page 17 and "old" corner book Page 193

Set post marked ¼ Sec. C.S., from which
 A Red Fir 30" dia., marked ¼ sec. CSBT bears N.6°W. 14 lks
 A Red Fir 24" dia., marked ¼ Sec CSBT bears S.55°E. 14 lks

Survey by John Markham - For: Stomar Lumber Co. - Jan. 16, 1959 - C.S. File 42/325

Cor. as determined by O.B.T.s
 34" Fir bears N.6°W., 9.2 ft. O.B.T.
 26" Fir bears S.55°E., 9.2 ft. O.B.T.
(Note: Markham calls the above trees "original" but they appear to be from Cain visit in 1913. V.Laugen)
At corner point Set 3/4" x 36" iron pipe, from which
 14" laurel bears N.54°W., 65.0 ft. mkd. ¼ S T29S R6W S23 BT.
 12" Laurel bears N.69°W., 107.0 ft. mkd. ¼ S T29S R6W S23 BT.

Fd. IP & 3 BTs by Howard Johnstone - 4/1978 - RM3-12

DCSO-GIS Corner visitation - 8/18/2004 - Typed: 2/2/2011 - C.S. File 67/33-1

Monument - BC/IP - ¾"
Comment - (needs) rehab

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2940, surveyed June/Sept. 2019- (DCSO records Vol. 59 Page(s) 24011-2)

The ¼ sec. cor. of secs. 23 and 26, reestablished by proportionate measurement by Cain, in 1913; perpetuated by Markham Jr., in 1959. There is no remaining evidence of the original cor. and this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron pipe, 1" dia., firmly set, projecting 5" above ground, from which a bearing tree mkd. by Cain Continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 46" dia., bears N.3°W., 10.8 ft., with a healed blaze.
and the bearing trees mkd. by Markham Jr.
A madrone, 24" dia., bears N.68¾°W., 104.1 ft., with a healed blaze.
A madrone, 23" dia., bears N.53½°W., 67.5 ft., with a healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron pipe, with brass cap mkd.
T29S R6W
¼ $\frac{S\ 23}{S\ 26}$
2019
and a new bearing tree
A fir, 8" dia., bears S.38¾°W., 22.9 ft., mkd. ¼ S26 BT.
Corner is located alongside of wire fence, extends E. and W.