

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6472)

Set ¼ sec. post at average distance, from which
A W.oak 18" dia., bears S.45°W., 28 lks. dist.
A W.oak 18" dia., bears N.30°E., 69 lks. dist.

F.C. Frear, Deputy Co. Surveyor - For: O.W. Ronk, Fred Smith and L.N. Sargisson - May 1919 - F.B. 46 Pgs. 47-57; Vol. 3 Pgs. 62-64 and "old" cor. book Pg. 130

Renewed from old BTs by setting a 1" x 36" galv. Iron pipe, from which
An 8" W.oak S.23°E., 19½ lks. C.S.B.T.
An 8" W.oak N.35 ¾°W., 41 lks. C.S.B.T.

Douglas Co. Surveyors Office - John Powell and crew - Feb. 8, 1971 - C.S. File 49/139-137

Found - No trace of 1" Iron pipe due to new Yewwood corner post at fence corner which falls directly at corner point.
8" now 10" W.oak S.23°E., 12.8 ft. shows good scar.
8" now 10" W.oak N.35 ¾°W., 27.1 ft. shows good scar.

Set Brass cap on South side of fence post marked:
County Surveyors Office
T 29 S R 6 W
¼ $\frac{S\ 11}{S\ 14}$
1971

This corner falls at fence corner, fences running E-W-N. Bearing trees OK and tagged.

Fd. BC by G Lang